



ENJOY RADIO CONTROL

A great number of people today are enjoy ing radio controlled models. They find excitement in the precise mechanism and excellent maneuverability of these models Some people enjoy customizing to increase their performance and, furthermore, organize races and competition. All of these categories offer limitless enjoyment to the fans. The reliable radio control unit which was once a very expensive gadget, has come to be within a reasonable price range as the science of electronics has advanced. Also new car and airplane kits are coming on the market one after another in increasingly refined form. The radio controlled electric car models are becoming more popular among not only novices but also skilled modelers because of high performance in spite of their easy handling. Many enthusiasts are attracted by the exciting operation and realistic make up of radio controlled electric

tanks, too This guide book is compiled to focus on the fundamental knowledge of the radio controlled electric model cars, on hints of asniques, and on racing, with our hope that the book can be instructional and help you enjoy the sport as well.

1 RADIO CONTROLLED MODELS Radio controlled models are nothing but

models remotely controlled by radio signals. So most operating models, if they are big enough to mount radio control units. can be converted for radio control. Badio. controlled models are classified under kinds of nower units: there are ones with with steam engines, and ones with no There are airplanes beliconters oliders racing cars, buggies, tanks, boats and some others, each of which has many

Mowever as for the radio control units most of them in use today are fundamentally the same; they are the digital proportional type, although their capability varies.

2. R/C ELECTRIC CAR Radio controlled electric powered cars are ideal for those considering RC modeling as a hobby. Its high performance can satisfy even the most discrimination enthusiast, and races can be held easily without air or noise pollution. For this simple reason, electric powered RIC cars have become very popular world-wide. There are many types of RIC car models on the market, and can be classified as listed

• 1/12 scale Racing car and 1/10 scale Formula ■ 1/10 scale Officead car and Bacino bunco ● 1/24 scale On-mad racing car If you intend to remain in the electric RIC car hobby for a long time, and compete in races. it is suggested that you select your car from cars run at speeds of up to 45kmh. They nexvide powerful, dynamic and thrilling driving enlowment. On the other hand, \$10 off-road racers and buggy cars let you run on any type of terrain, such as unpaved areas, sand, hills, dry can not go. They have larger body sizes than on-road cars so they can take the rough road running and obstacles. Off-mad racing and budgy racing provide you with more of the much and tumble actions as compared with coupad car racino Tamiva 104 scale Tamtech cars have become

popular compact scale RIC models. Its compact size allows you to enjoy it in or outdoors. components are the same as on the larger scale RIC models, so that none of the excitement is lost.

DIFFFRENCE BETWEEN RADIO CONTROLLED MODELS AND TOYS

There are many radio controlled toys sold on the market these days. The characteristic of toy products are inferior in capability to models: for instance, they can turn only in one direction or run very slowly. Of course, some of them are close to the border sive factor is that the toy is always sold presented in a kit form with components unassembled which are left to you to finish, no matter how little the assembly may be. So the model may be finished in varying levels of the assembler. Also, they are able to be improved and customized with accessories

RADIO CONTROL SYSTEM When you have bought a model, a radio control system designated for the model should be purchased separately which then is to be installed into the model.

such as an airplane or car Most predominant radio control systems on the market today are the digital proportional type. In short, they are called a radio. For radio controlled electric cars and tanks, a two channel digital proportional metern is normally used

1. MAKEUP AND OPERA-TION OF DIGITAL PRO-PORTIONAL


Battery level meter Steering stick

consists of a transmitter which is to be operated by a modeler, a receiver, and servos which are mounted into the model, plus power supplies for the units. A transmitter functions as control box, fitted with operating sticks (trigger or wheels), and trim levers for fine adjustment. When the transmitter is in operation, it emits signals by means of radio waves. The nical movements. A servo motor in the servo rotates in either direction at some velocity for some duration of period according to the signals given. The mechanical movements are put out from a serve horn to a model unit to be controlled. Thus, the whole model can be manipulated. The word "proportional" of "digital proportional" indicates that a model is controlled in proportion to the degree that sticks of the transmitter are moved. When you move a stick quickly, the servo motor rotates quickly. When the movement of the stick is stopped half way, the movement of the servo horn will trol a model car at will by manipulating a stick of the transmitter quickly or slowly, to full range of throw or half way; the movement of the seryo horn is hooked up to be transmitted to, for instance, front wheel/steering of the car. This characteristic of movement has made the digital proportional radio control system the prin-

2. THE NUMBER OF CHANNELS-THE NUMBER OF CONTROL OPERATIONS

cinal type in use today.

The number of channels of the radio control system indicates the number of



operations to be controlled at a time. A four channel digital proportional system will employ four serves to control four different types of action. The radio controlled electric car is basically designed to be controlled in two ways, speed control and steering control; therefore, a two channel radio control system is to be employed. In the present market, radio control sytems are available with up to eight channels. The two channel type, though the most fundamental, is enough to control cars, tanks, hoats and oliders except gas powered model airplane (which usually require over three channels).

3 ABOUT RADIO ERECUEN. CIES.STATUTORY RANDS

FOR RADIO CONTROL Radio waves are used very widely in the emergency, police and military, let alone radio and TV broadcastings. If these radio waves should be interfered with, obvious problems could develop. Therefore, specific frequency radio waves for different purposes are regulated to be handled by qualified personnel for the purpose of avoiding disorder. Thus a number of frequency ranges are designated for model radio control, and any other frequency ranges than the allocated ones should not he used under any circumstances.

4. FREQUENCY BANDS

This phrase "frequency hand" is used to denote the frequencies of radio waves. A receiver of the radio control system will accent signals emitted even from another transmitter, if the frequency used happens to be the same, the servos will also be put in motion. In other words, radio control systems on the same frequency will resoond to each other thus causing them to no out of control Movemer a number of radio control systems all using different frequency bands can control many models. Monon it is recommended to employ radio control systems with dispersed frequencies to avoid interfering with each other when omanizing racing events in croups.

5. SAFETY, REGULATIONS AND OPERATIONAL BEHAVIOUR

Some radio controlled models of airplanes. racing cars and boats powered by gas enit can cause serious accident if they should might involve personal injury. Even electric radio controlled cars can attain speeds of 30 km/h. Be sure to abide by the rules stated below and be careful not to endanger or annow others

*Do not use the streets for running

*Do not operate near children or in *Auoid radio interference *Inspect your transmitter receiver and models prior to operation.

ADADIO INTERERRENCE IS DANGEROUS

Signal waves of radio control systems sometimes reach about 2 kilometers in the

air and over 300 to 500 meters on the ground. When there is another person on erating a radio control unit, compare the frequency of your radio control unit with his Avoid the possibility of interference: operating radio control units of the same frequancy will inevitably result in interference and get your model out of control. In such a case use an alternate frequency if possible. ◆ In radio controlled models. the fixed fracuso. cies are used commonly among cars, air planes, boats, and any other kind of model So radio interference will occur so long as the same frequency is used regardless of the difference of types of models. Radio signals

from other types of radio control units will interfere with your radio control model. CHECK ON INTERFERENCE A device called a "monitor" can be used for detecting radio interference. There is an-

other simple was more your transmitter must

from the model to some distance, and watch the response of your serios. If the serios move strangely, interference can possibly be recognized. While operating your models, if you recognize any sign of interference aton running and check the cause

6. POWER SOURCE In most cases, two different batteries are used

for running a radio controlled electric car one is used to nower the radio control receiver and the other powers the car's motor. For the radio control system, about 8 to 12 LBM3 (AA) size dry batteries are used (8 in transmitter and 4 for received. The 4 receiver hatteries can be eliminated by using an BIC unit equipped with Rattery Filminator Circuitry (REC), or by adding a Tamiya Battery Eliminator to the standard RIC unit. The RFC systems enable the receiver and servos to draw their power from the Ni-Cd running battery





HOW TO SELECT AN **ELECTRIC SOURCE FOR** POWERING CARS Nickel-cadmium batteries can be used for the power source of radio controlled electric cars. There are two types of nickel-cadmium batteries: one is a nackage type and the other is an individual type which has the same shape as dry batteries. Dry batteries are cheaner in cost but not economical since they are thrown away after complete discharge. Also in performance, dry batteries cannot power the car as fast as nickel-cadmium batteries do. It teries for operating a full fledged radio control model for creater running time

TAMIVA NICH BATTERIES Tamiya's Ni-Cd batteries utilize the tabless

system for obtaining the maximum current flow resulting in more powerful acceleration and higher total performance. If the battery is handled correctly and cared for, it can be recharged more than 500 times, making it very economical even though the initial number. inc price might have seemed expensive when compared to dry cell batteries. For the running power source of RIC models, Tamiya provides poses. Large capacity 6V-4000mAh batteries used for plant BIC models, flat type 7.2V5200 mAh Racing Pack and 7.2V1700mAh Racing Pack EX batteries for competition use, and for those seeking more power, 8.4V1200mAh Gold Dower hatteries are available to addition there are the 7.2V-270mAh Tampack batteries for Tamtech cars, and fly Mini Packs for RIC units. 6V, 7.2V and Tampack quick charger units are also available.



MECESSARY TOOLS AND

Not many tools are required so long as you assemble a kit as is. The necessary tools are illustrated below. Tools especially in need are included in the kit, or at least an explanation about tools is given.



ers (radio type and ordinary types), screwdrivers, diagonal cutting pliers, files, vinyl tape,

Some specific tools Tamiya recommends are the Side Cutter (74001) for snapping wires or removing parts from plastic parts trees, and Long Nose Pliers (74002) for holding parts dur ion assembly and for twisting wires. The Apoli ed Tweezers (74000) or the Straight Tweezers (74004) make picking up small nuts, screws or other tiny parts much easier. Curved Scissors (74006) are handy for trimming polycarbonate bodies, and the Screwdrivers (74006 74008) make construction tasks easier

Handy tools if available are side cutting pli-



GLUE As for glues, the following three kinds are adequate for assembly: plastic glue, instant glue

and synthetic rubber cement. Some model kits include a tube of glue; on top of that liquid plastic cement is quite useful. Instant glue is used for example to fix a semi-preumatic tire to the wheel, and synthetic rubber cement for a sponge tire to the wheel. . Be careful when using instant glue, since it has stroop arthesion, requiring only a moment to do. Therefore it is dangerous to

have it in the eve or on the skin **CLIQUID THREADLOCK** Synthetic rubber cement can be used for

lock" works better for keeping bolts and ruds from coming loose.

OII FR It is a must to oil near how shaft, and bear ings. When all is insufficient, it hinders performance, and can result in serious trouble such

as seizum of shaft. Sorry type oilers are also available on the market today which are very handy for upkeep of radio controlled model cars. FINISHING

application are available.

Use plastic paints for styrene resins, and polycarbonate paints for clear Lexan RIC car bodies. Soray type paints are convenient for finishing larger areas such as bodies. For painting details like figures, bottle paints for brush

PLA-PLATE, POLYSTYRENE SHEETS, PLASTIC PUTTY

Pla-plate is plastic sheet of the same material as plastic kits. It can be expediently used for creating your own designed wing to the car and for reinforcing bodies and so forth. Putty is handy for mending scratches and small cracks which are often found after remodelling kits. Several kinds of plastic cutty are available on the market.

7. ADVICE ON SELECTING TAMIYA CAR KITS

Electric RCC care generally are available in loss coles alsos. 190 or 190. Both scales are used scales after 190 or 190. Both scales are used world wide and regarded as the most practical size for both on and off road vehicles. When buying your first kil, it is important to select a residual setter. A store that provides good servicing to customers, carries an ample stock; or parts, and its willing to help and guide beginners, and the selection of the provides of the provides of the provides of the provides of the contents and proferomance about it, and study the contents and performance of the models to that study the contents and performance of the models of that should the contents and performance of the models of that should be sufficient to the provides of the models of the models of the models of the models of the study and performance of the models of

All Tamiya RIC models and kits are of the highest qualify and are among the easiest RIC models to assemble, regardless of category. All are supported by an escellent range of batteries, chargers, accessories and spare parts.

ASSEMBLY KITS AND COMPLETED MODELS

There are assembly kits on the market which you build up parts into a model by which you build up and into a model to have a seen and the parts and the part

READINESS OF PARTS AND COMPONENTS

Select model, the parts of which are easy to obtain. Tires and gears can wear out even a speed control swirt in an expenditure of the parts of the p

and accessories are easy to buy at model

OHOW TO SELECT A RADIO CONTROL SYSTEM

The most popular type of each control system beginners and even intermediate modeliers, beginners and even intermediate immodeliers, this type of system provides the most control this type of system provides the most control modeliers should be consider the wheel control system for better performance. Installed of stocks for controlling selecting and through the control system for better performance. Installed of stocks for controlling selecting and through selecting selecting and through selecting se

♦ HOW TO CHOOSE BODIES
There are two kinds of model car bodies:
Icear bodies are made of polywiny!
Chloride bodies are made of polywiny!
Chloride or polycarbonale, featuring lightness. However, being vacuum-formed from railess.
Lower bodies in finish of Idelikeness and detailings, while hard bodies (plastic bodies) offer much more precision scale as they

POINTS IN PURCHASING The assembly kit consists of numerous

The assembly kit consists of numerous parts and accessories. So it is recommended to check up on the contents of a kit with a store attendant at the purchasing point. Also read through the assembly pamphlet to see how difficult or easy it is and ask questions, if any. Also you might as well inquire about the technical guidance and

BEFORE ASSEMBLING VOUR KIT

Here are hints for easier construction of your RC car kit. When you open your kit box, check your kit for completeness against the parts list in the kit instruction manual. Become familiar with the parts and their names so that when you begin assembling your kit you can follow the instructions easily. As you begin to assemble the car, you should

follow the instructions easily.

As you begin to assemble the car, you should put small parts into a separate tray or small box so you can find them faster without losing them on your workbench. For easimple, you all parts for Screw Bag "A" into a tray and mark the tray with the complete label from Screw Bag "A" for easy reference. Do the same for small plastic parts and bister ocative and set.

As you put parts together, test fit them into position before permanently assembling them. When the parts are test fitted, carefully compare how the assembly appears against the drawing in the appropriate

assembly step. If the assembly does not look connect, examine the parts more closed by ou use the connect parts. Phintaps you on the parts together in the incomet sequence that the parts together in the incomet sequence drawings in each step closely to assed such classification of the control of the control a life in which you will take pleasure. When you attack shows and ruls together, harring Lupid Threaddock to keep the conseand ruls from locening due to shock while the car is number, Do not use other barrols of "freeddick because they will diamage of "freeddick because they will diamage."

TEST RUNNING HINTS

• Before installing the motor into its mourt or a gear box, it should be allowed to run freely in each direction of rolation for 15 minutes. • Light grease should be applied to the teeth • Light grease should be applied to the teeth to all adds, and bearings. The oiling procedure is very important for sintered procesbearings, also known as oiless metal bearings. The oiless metal bearings actually reriging. The oiless metal bearings actually rewritten away all excess plastic fitsish from the rejoto bushings, otherwise all autes and

nylon bushings, otherwise all axies and gears will not rotate smoothly!

*Make sure the motor pinion pear merhes smoothly but not too lightly with the gear box. Check the pinion gear to avoid contact with any edge of the giar too or cover. bited and the motor installed, the parts should rotate easily when the motor is powered by a single *D* cell battery. Make sure you perform this check!

sure you perform this check!

*Before using your vehicle, we suggest you
run the motor and gear box in the vehicle
with no load for 15 minutes to break in all
the gears. Make sure to set the vehicle up
on the box with the tracks or tiers above the
ground to allow fire movement of the gear
box when running in.











VERSATILITY OF TAMIYA PRODUCTS

HOW BEST TO ENJOY
RADIO CONTROLLED CARS

Speed race, gymikhana, drag race, and rally are the ways you can enjoy racific controlled cars. They are roughly classified into two groups by nature of races. In speed races and drag races, a number of cars start at a time to best each other in time elapsed, and in gymikhana and rally, cars start one by one to compete against time. The Tamiya radio controlled electric cars will protifice under the control of the control o



do a number of different racing events, depending upon the size of area, large or

IN LARGE SPACES

It a large open space is available, only speed racing (heat racing). The road course (winding course like a circuit) and simple oval course are typical for use. In this kind of competition, the first to competition, the first to compete accertain number of laps in the winner. On the oval course, the laps race is also run, in which two cars staff at the same time one which catches up with the other being the winner. If it is difficult to make a road



course for only one car, it is recommended to enjoy high-speed gymkhana. Set a course with obstacles of empty bottles or anything similar. The winner is determined by the time required to complete the

course.
IN LONG NARROW SPACES



Salom race

if the space is long but marrow, you can be disposed to provide parange or salom racing, in the disposed parange, the object is to cover a long straight parange, the object is to cover a long straight parange. The object is to cover a long straight parange of the long strain strain

a course only about two meters wide. IN SMALL SPACES

You can enjoy Tamiya's radio controlled car even in a space only about 2 meters





square. If the space is limited, it is recommended to race technical gymkhana, Make a course with many curves which need good control technique. The winner is determined by the lowest time required to un the course. Caraging gymkhana, backing gymkhana, etc., may be a lot of fun. too.

RALLYING

In raily, the car which runs the course in the closest time to a certain fixed time is the winner. The same timing method as the rilly can be employed to determine winners target time after a few timings of trial runs along the course. Various rules can be established, for example, the penalty system is adopted for a time nequired over the far-get time, or in both cases of over or short of a target time or or conditions of a target time for conditions of a target time.

the game may be made more enjoyable. HOW TO USE RADIO

CONTROLLED BUGGIES

An off-the-road buggy race has much ex-

citing fascination, a different pleasure than racing cars. Compete over a dirt course and cross country race to enjoy exciting driv-



DIRT SPEED RACES

Dirt speed races can be done in flat and vast areas such as a playground or a park. The course can be made in a simple oval course or a more complicated track with hairpin curves and figure "5" curves. You have to be careful since the surface of a dirt course is slippery. Advanced techniques of control are called for, but if it is fur.

OBSTACLE RACES

in a place which does not have a very large open space, make an obstacle course. Usilize dents and humps on the ground. Along a curving course with ups and downs, a car will run in an unexpected direction and it is fun to drive cars on it. You can make it more interesting by spreadings and and pebbles.



Transport of the Contract of t

DIRT GYMKHANA

in a small place or when there is only one car, make a gymkhana course with empty bottles and drive a car through the pylons. By changing the arrangement of the bottles, a backward course may be made. Compete for time one-on-one.

HILL CLIMB

It is a slope ascending race. Any one which arrives at the top of a mound or a slope is the winner. Or you can contend for ranking by how far you can neach on the up-slope in a fixed time. A decisive factor can be the selection of a high gear or low gear combination, and to take a straight way or a zigzag



SPECTACULAR JUMPS

Thrilling jumps are another way of putting on a show with a buggy. Have take-off planks in your course. However, do not make it too high. Build a fairly long straight way before the plank to provide an approach run.



Do not run the model car in the following

places: In a pebbly area or with a very bumpy surface, since the suspension system of the car may be damaged; or in a grass covered field, because grass blades may be caught in the car; also, not in a crowd of people or

nearby children.

HOW TO ENJOY R/C TANKS Tamiya model tanks are powerful enough to

force their way over rough terrain and to climb cohatacles. They will offer you the widest diversity of enjoyment. You are challenged to create various ways of racing with the Tamiya radio controlled tanks which can be made to made to english and left, do gradual and pivot turns and, of course, go forwards and backwards.

ON LEVEL PLACES

The simplest statom games can be enjoyed. Use empty bottles for pylons and run your tanks in the same way as your radio controlled cars. The first to complete the course is the winner. If a bottle is knocked down, one point is deducted from your marks. You can make the racing more interesting by adding slopes to the course.

IN ROUGH PLACES

tanks on a rugged surface. Obstacles, such as boulders, steep slopes and trenches, can be made a part of the course. A rule could be made to lose marks when a vehicle goes off course or runs backwards. When a tank stalls on the course during a race, the driver is disqualified. The winner is determined by measuring the time taken to complete the course.


DRIVING TECHNIQUE

HOW TO IMPROVE DRIVING **TECHNIQUES**

You cannot make yourself a skilled driver just by running a car at will. Make a course using things like empty cans as pylons.

BASIC TRAINING OVAL COURSE 1

This is the simplest course using two pylons. It looks simple at first sight to drive a car along. but it will require some practice to achieve sharp and riold turns made with the relons as vertexes of the curves. Practice both ways, clockwise and counterclockwise, until you can make both rounds in about the same period of time. Figure



OVAL COURSE 2 Have two or three pairs of pylons forming gates and run your car through them as accurately as possible. You will find it much harder than the oval course No.1. For the first period of time, arrange the pylons at a wide



ROAD COURSE

When finishing course No. 1 and No. 2 you have mastered the basic driving techniques. Now you should proceed to complex courses. Build a road course with the pylons, from basic figure "T" and "L" courses to more complicated circuits, assortment of figure "L" and hairpin curves, high speed course and slaloms.





WHERE TO LOOK AT WHEN

DRIVING When you drive a car, it is important where you keep your eye on. Suppose the ovals describ sight on the forward part of the area of vision with a car placed at the rear. The car moves at a rate of 8.3 meters per second when the hourly speed is 30 kmh. With your point of sight on the car itself, you cannot keep clear of obstacles ahead, because it is too late to notice them; nor can you take comers easily





CORNERING TECHNIQUES

No particular skill is required for driving a car just straight, and the drag speed is limited by the car's own inherent performance capability. However, at curves, your finesse of taking corners affects the result even among cars of the same performance. Especially in speed races, the cornering technique is one of the decisive factors. After becoming accustomed to the car, try to practice smooth, speedy and stable comerings.

THE BASIC PRINCIPLES OF SLOW-IN AND FAST-OUT "Slow-in and Fast-Out" is a golden rule in

speed controlling at curves. And "Out-in-Out" instructs how to steer a car Briefly you should control speed in "Slow-In and Fast-Out" manner and steer a car in "Out-in-Out" way



WHAT'S "SLOW-IN AND FAST-OUT

Decelerating when entering into a curve and picking up the speed after a vertex of the curve is the technique. In the case of entering bends without reducing speed, the car is forced to slow down before finishing corners to lose speed and stability. In the worst cases, the car might spin or run off the course. It also gets the car moving too late to pick up speed. As a result "Slow-In and Fast-Out" is the fastest way to take corners.



WHAT'S "OUT-IN-OUT"

It is, as illustrated above, a way of turning the inside line to which the car will come closest at the vertexes (crimping points) and finishing the cornering approaching back to the outside line, thus making the longest possible turning radius. By utilizing the full width of the course, the car will make an easier turn than the actual curve. So the car may be allowed to run through it faster. As a matter

of fact, however, it seems more advantageous because it allows easier latter half cornering and enables the car more powerful acceleration into the straight course, in spite of sharper first half cornering.

 Both "Sinula and FastOut" and "Out InOut" more importance to velocity in the latter half of cornering than the first half. This has something to do with the acceleration of a other cars at the latter half can take the lead in the successive straight track, provided the cars should have the same pickup and maximum speed capability. This principle is true you are not required to reduce the speed at

THE LAST CURVE IS THE MOST IMPORTANT IN A CHICANE

The last curve is the most important in continuous curves. In successive bends of a madturn at the last curve. Then you will be able to speed it up as soon as getting into the straight course



CONSIDER COMPLEX CURVES AS ONE

Consider complex curves as one integrated compound. In the case of complex curves with different radii, you can manage to get through by considering them as one complex curve and making a cornering passage.







CURVES WITH A STRAIGHT COURSE IN BETWEEN Even in the case of recurrent curves with

straight tracks intervening, you could achieve a smooth cornering by counting them as one integrated curve. DURING A PRACTICAL BACE

TAKE THE CLOSEST POSI-TION TO THE INSIDE LINE Get to the inside tane while still on the

ing technique explained is the ideal way when a car is running alone. In actual races however, when several cars of naturally other racing techniques have



important point is to get the closest posiof the other competing cars. Here, as ilthan A's and car B will be forced to slow down, but with the advantage of a smaller radius, may be able to get ahead of car A by risking a scinout or being hit from behind by car A. It may block the other oncoming cars. Slower cars should yield the ight of way to the faster cars.

OTHER CORNEDING TECHNIQUES

As for other cornering techniques, there exists four wheel drifting and tail sliding like technique steering a little excessively at the early stage of a curve and letting all heading for the inside line of the course. In this way the car can get through the curve most quickly; however, it is difficult to practice. The tail sliding technique is to make the rear wheels skid while countersteering. This technique is not as stable as compared with the four wheel drifting. and it may not be fast enough to get through the curve, although it looks spec-

OPPOSITE LOCK STEERING

The word indicates to steer the wheel against the curve of the turn. If a car should go too fast on a curve, the rear wheels might start to skid, to counter the spin steer into the direction of the skid















WINNING BACES

IMPROVE YOUR DRIVIN

1. PRACTICE AS IF YOU

WERE RACING
After you have add not mastered. Onlying Rechapter, the next step is to actually proceed to be a strong of the step of the ste

racing as you can.

Competition practice
A race is run with many cars at the same time.
If you want to become familiar with racing, the

If you want to become familiar with racing, the best way is to hold practice sessions with your friends as a group, it is important to feet the difference between driving a car by yourself and competition racing. You'll notice that the tacks seams convented narrower with all those case and it becomes difficult to sheer the car on the fire you begins. Busement is what addition, practice racing will feach you many things about quick starts, how to small property or the things about quick starts, how to small case change of the Change practice tracks.

Do you practice your driving technique at the same place? You should change it sometimes. On-road races and off-road races are not always held at the same place. Surfaces of the track whom races are held are much different from the surface on which you normally drive your car. In many cases, even though you drive and control your par perfectly during practice running on unfamiliar surfaces can become a hassle with your car spinning out of the track. Practice driving on different surfaces is essential to improve your racing skills. Bunging on different tracks gets you tuning the car according to differing running surfaces, which in turn provides you with confidence and easier control

2. RACING TECHNIQUE

is difficult to display your ability to the full in actual racing. When several cars are together, the raceocurse appears narrow. Your car is sometimes involved in an accident, and you may often fall to drive your car along the desired cornering line. To achieve good results in racing, it is necessary to acquire good racing tactics and

Sprint and long distance

racing
Races are roughly divided into 2 types, according to the length of the race: sprint and long

distance in the real motorsport world, both races are very occular and numerous events are held in many countries all over the world. As far as sprint races in the world of RIC goes. the cars are raced from 3 laps to 15 laps, at most without a battery change. Sprint racing is a flat out speed race requiring techniques that also become useful in long distance racing. First, you should start with sprint races. This will develop skills and experience for all types of racing. As you now know, the distance traveled in a sprint race is much shorter than in a long distance race, therefore, a very minor mistake can ruin your race, and recovering from that mistake and winning is going to be a very difficult task. Each competing driver is trying

hard to get the utmost performance from his car, using his radio control skills and driving technique to take the checkered flag. 1 Points in practice laps in most races you will be given a chance

In most races you will be given a chance to practice over the course, but you don't have to run the car very fast. What is important is to make adjustments by means of the trim levers and to gain knowledge

Adjustment with trim levers Practice is the last chance to make any necessary adjustment by running the car. Make sure the car runs straight and the speed control switch can be turned to maximum speed. If necessary, make fine adjustment by means of trim levers. If the switch contains a brake circuit, make sure that the control of the control of the switch contains and the control of the switch contains a brake circuit, make sure that the control of the control of the mended to run it directly away from you.

of the track.



Nowledge of the race track Course errors in racing must be avoided. It is important to do practice running along the course at least once. Particularly if you are on this track for the first time, it is necessary to run the car positively along the course in advance without hindering the progress of races, as well as to attend possible, to walk along the course in order or remember its intricacies and to note its.

Checking out track

The weather has an important influence upon the surface condition. It is not too much to say that tracks vary according to the weather on the previous day. You should check out the track condition and decide in advance how to negotiate the main corners. Consider changing the tires, if you have time, according to the track conditions.

The result of a race sometimes depends upon the start. However, a quick start is not always advantageous. Accidents are the lirst corner because participating cars are running close to one another. Decide how you should start according to the characteristics of your car, course layout.

When a quick start is advantageous

activation percent in the starting acceleration of your car and you believe it is able to out-distance others before the first corner, then you should choose a quick start. Also, if the distance between quick start is advantageous. In this case, even if several cars have made a quick start, the distances amongst them graduably increase and, therefore, there is not start, the distances amongst have made a quick start is advantageous also when

A quick start is advantageous also when the distance of the race is short or when the course layout is intended mainly for speed competition.

When a slow start is not

When a slow start is not disadvantageous
When you have tuned your car with a

greater emphasis attached to its maximum speed rather than on its acceleration, it should be easy to make up for leavy on a straight even if you have made a slow start. In a long-distance race, you don't have to be very enerous about the start. Also, if the distance between the start and the first corner is short, it is advisable to make a slow start to avoid collision on the first corner.

Whether to run ahead or behind a rival

Some drivers prefer to run ahead of their rival rather than behind him, whilst others prefer to be in pursuit. They have their own nace setting in races. The former drivers direct their energies particularly to the first half in order to take the lead from the beginning. Drivers of this type need to employ tactics so as not to be nassed by their rival. They should synid leaving a gap on the inside of a curve where they could be passed. Note that if a driver brings his car into contact with any other car on purpose, he may he disqualified from the race. The latter drivers on the other hand, make a slow start, pur sue their rival steadily and wait for him to later. Drivers of this type aim at constant performance. They must be able to pass their rival whenever they get a chance. It is nood advice to follow close behind your rival's car hoping to cause him to commit an error and thereby getting a chance to overtake him. Decide whether to be ahead or behind your rival, and employ suitable

tactics.

 Take and hold the inside line during comering

When competing with your rivals during cosnering, take and keep the inside line for maintaining the lead. It is difficult for you to beat your opponent in the corner by trying to pass him on the inside line because both cars are nunning at about the same speed. If your car can manage a higher maximum speed than the others, only then, is passing on the outside line possible. Trying to take the inside line too early can lead to over-running the corner resulting in loss of time and running space for your car. While you're at the edge of the track. your rival can easily pass you on the inside. In order to avoid this, stick to the inside, foroing him to delay his acceleration. Taking and rule for taking the lead at corners. Confrontation between cars during cornering are the most exciting moments during a race, but be sure to avoid the selfish type of running that can cause collision and damage that will spoil

■ How to pass others *Passing on the straight: There are various places in which you can

the overall race for everyone.

try to pass another car. A straight is the safest place to do so. It is dangerous to start passing a car when you are following close behind it. When you judge it is possible to pass, steer your car a little as soon as possible and attempt to pass. You may pass on either side, wherever there is more room. If the space on each side is about the same, it is advisable to our inside to make the next come raiser.



Passing on a corner is dangerous as compared with passing on a straight. If the driver of the car you are going to pass is in on taskillful in control, your car is labele to be involved in its spinning. To make passing assier, it is advisable to go inside the rivar's car and pass it after turning the corner. It is very difficult to pass it on the outside of the corner even if your car is much faster.

+Passion on a corner

If your car has hit another car and lost its stability, then reduce the speed by turning off the speed control switch. If you try to restore stability by steering, the car must be further disturbed. Start acceleration again only after the car has slowed down and is stable. On the track

With the exception of a plain oval track, a typical road racing course is made up of straight stretches and numerous turns that test your radio control driving skills. Before going onto the track to race, look it over carefully with the potential of your car in mind. If your car has power and high maximum speed, you should stretch, and if your car has less power but superb handling, you should concentrate your driving at corners. Taking the inside line quickly and swiftly at each corner will enable cars with less power to take the lead. On the other hand, cars with high output should fully accelerate at the exit of the corner to obtain the utmost speed in the stretch. Know your own abilities and the track. Know when to use maximum power and when to concentrate on handling. Study the track thoroughly and decide what part of the track requires your utmost driving ability. Running at your limit all the way will only spin you out of competition.

Currently, sprint racing is very popular among RIC car enthusiasts. Usually these races consist of 2 to 3 racing heats to determine qualifiers for the finals. Each qualifying heat has from 3 to 5 laps of racing and the finals will have from 7 to 10 laps of racing. Set your own pace for each heat to obtain the best results your skills can offer.

First heat

It is impossible to foresee what accidents or trouble will occur in your race. If you damage your car in the first heat by overtaxing it, perhaps you may not be able to achieve a good result in the end. Steady running is the key to success. Use the first heat to verify that your car is handling correctly and running smoothly, and just endeavour to complete the race. Never overtax the car, If it fails to finish, there is little possibility of being allowed

Second heat If you run the first heat steadily, you can

a better result than in the first heat, use all your skill and employ more aggressive cornering techniques. If you did not ob tain a satisfactory result in the first heat, you may stake your all on the second heat, but you must not drive recklessly You should refrain, as far as possible from using tactics that might cause an accident Final race

Being able to take part in the final race already means that you are a qualified driver. Show ability to the full in the final race. From the results in the first and second heats, you can guess your ranking among the finalists. If your ranking seems low, endeavour to raise it, even a little, without aiming at victory. If you seem to rank high among the finalists, you should try to win. As you are capable of winning. or at least a good place, be careful not to be involved in a stupid accident. Always

do your best.

3 DRIVING ACCORDING TO

There are various track surfaces: asnhalt. concrete, wooden boarding, vinyl tilling, etc., and they all have different characteristics. Practice repeatedly so that you can control the car on any kind of surface. Generally speaking, asphalt or concrete tracks are not slippery because they are rough and have a high coefficient of friction. Wood, vinyl-tiled or cement surfaces are smooth and slippery. Note that even asphalt race tracks are slippery when they are wet or covered with fine sand or dust. It is possible to gauge the track condition by eye, but it is very important to check out the difference of the surface from your usual practice ground by making a test run

Quick acceleration, quick

On slinnery race tracks, the orin of time is very small and the stability of the car is disturbed very easily. Quick acceleration is taboo even at the start, because the rear wheels (driving wheels), whose tires have little grip, are liable to spin and the car may slide even when it is turned only slightly. Be even more careful in deceleration. If the cay is quickly decelerated, the load of the car will move forward by inertia, (in other words, the center of gravity will move forward), and the load on the front wheels will increase while that on the rear wheels will decrease. Therefore,



Comering on a track with good adhesion. the grip of the rear wheels will become

much less and they will skid very easily. Deceleration must be made as slowly as possible. Never brake the car quickly when it is running at top speed Reduce speed sufficiently before corner ing. In cornering, the car is subjected to centrifugal force which pulls it outwards. It is because the centrifunal force is creater than the crip of the tires that the car is liable to spin or run out of road on slippery surfaces. The centrifugal force increases in proportion to the speed Therefore, it is necessary to decrease the centrifugal force by reducing the speed and making the turning radius as large as possible. Needless to say, quick acceleration and quick braking are taboo in cornering. Reduce the speed sufficiently before entering the corner, and increase the speed after completing the turn. It is a cardinal rule that the cornering line should be "out-in-out" so as to make the

turning radius as large as possible.

ACCORDING TO TRACK

The tires have a great influence on the performance of the car. Even when the surface is slippery, it is possible to reduce the chance of skidding by using suitable tires. Many people use sponge or pneumatic rubber tires. Use either of them according to the surface.



Sponge tires are suitable for asphalt or

concrete tracks. They are softer than pneumatic rubber tires, and adapt themselves better to the track surface. Therefore, on asphalt, etc., with fine grain, they grip firmly. However, on smooth surfaces, such as wood boarding, they are inferior.



such as over-steering and under-steering.

Spike tires

Excellent for good grip on soft soil surfaces Spike can really dig in. The tires have spikes molded onto the tread surface. The spikes help the tires get the best traction on loose surface nunning, improving acceleration and handling of the car. The spike tims though, have disad vantages of wearing faster, and a car with spike tires can experience a roll-out when running weak princing on hard surfaces. Spike tims are

strictly for off-the-road chores. Block pattern tires Off road surface gripping for block pattern tires

is not as great when compared to spike tires, but can cope better with differing running surfaces. Block pattern tires with tall blocks mold ed at wide intervals provide good grip, and have a hetter wear factor than the snike tims when run on hard surfaces. Consider it when the track has both hard and soft surfaces.

Ω

Lug pattern tires

The tread pattern on these tires are molded laterally and can be often seen on igens and trucks. Also there are the so called "Sand tim" or "Paddle tire" that belongs in this grouping These tires have the large blade patterns seen on water wheels and molded on fat balloon tires. These help the car over soft sandy terrain without digging in and becoming stuck The lug pattern tires provide good traction, but have less gripping perseverance to G-forces.

Rib pattern tires These tires have a lengthwise rib pattern

moiding, and are often fitted to the front end of off road going cars. The lengthwise ribs and grooves help the car maintain its grip and control from side forces, providing excellent straight running ability on rough roads. The oval block pattern pro-



Low height tires

Also called the "Low profile tire" these tires feature lesser side wall heights than the others. and provide firmer grip on tight corners due to less deformation of the tires during G-forces. Larner wheel and less tim when compared with other wheel and tire combinations, which leads to weight saving. Low side wall means stiffer tire characteristics, and thus less shock absorbing is done by the tire. Therefore it is important to keep the suspension unit maintained to accept those extra humos on the trails.





GUIDANCE TO PARTICIPATING IN RACE

Today the radio controlled electric car races are often held in many places promoted by manufacturers and hobby stores Participate in the official competition when you get used to operating model cars to will gain confidence. Even with poor grades, you will see better modelers operating a car which is most likely of better performance and helps you to improve your own control technique and your model. You will also find a different kind of delight other than playing with models among just 1. APPLICATION FOR

hobby stores or in the magazines. It is mandatory to enroll yourself in the contest roster; in most cases you cannot apply to


to give the class and kind of your car and frequency you will use, besides your name and age


2. CONFIRMATION OF RULES AND REGULA-TIONS

123456AB









Rules of facing events usually tell you how the race proceeds, how to determine the winners, how to group the models, kinds of motors and hatteries to use. Sometimes detailed regulations are provided to requi late the standard equipment of racing cars Confirm these rules and regulations beforehand with your car, and remodel or modify if necessary for compliance. In official competition, car inspection will be done at the registration area on the day to competition. Therefore, if there is any point you don't understand in the rules and requlations, you should check it with the host or-

4. PREPARATION BEFORE

bring tools, glue and oil which you use every day. Sometimes you have to mend THE RACE your car even in the midst of competition. Get your car ready for the race by the pre-Do not forget to bring fragile parts and vious day. The most important is the radio accessories which are easy to lose such as to the length of time of the event, that

spare batteries may be recommended to have for caution's sake. 6 REGISTRATION AND CAR CHECK

Leave your home for the race site with ample time for arriving early for registration. Your delay for the registration may upset the whole schedule and annoy others. Very often registration and car check are conistration desk, you may be given a contest number, perhaps marked on a pennant, During the whole event, you may be referred to with that number when being called

this number. Car check may be done after the registration. Your car will be examined

place the transmitter in custody of the host

ornanization Namely you cannot tune it un

on the competition site after registration

On top of that, gear meshing, screws or

bolts and nuts, shaft and tires should be

carefully looked over; repair or replace

with new parts, if necessary. Of course, oil

all the rotating parts. If you find batteries

are low on power, replace them or charge them fully if rechargeable.

5. THINGS YOU MAY NEED AT THE BACE TRACK

It is needless to say to take a registra-

tion card or membership card with you, if anything like that is required. Be sure to



with batteries on board. Even if your car should be disqualified, you might be adyour car on the snot in accordance with the rules of the organization. After the car check, you are called to hand over your transmitter to the officials. Be sure the switch of the power source is off before handing it over. The reason why transmitters should be impounded by the organization is to avoid interference by intentional or unintentional sighals during the races. is used as a receipt to retrieve your trans-

7 BRIFFING FOR DRIVERS

Prior to the races, a briefing is held for lett ing the contestants know the procedures of the competition. Listen carefully, since how the races proceed, penalties for violating rules and other important affairs are explained.

8. MAKING UP A RACING GROUP In a radio controlled model race, cars on

same time. Therefore, those who use different frequencies will make up a competing group. Before the races the combinations of the groups are announced. You should confirm which race you will be in. When time is getting close to your turn, prepare yourself for the race.

9. JUST PRIOR TO YOUR

Your name or number is called to inform you of your turn. Beceive your transmitter according to the official's direction; switch car. Move the sticks of the transmitter and see if the speed control switch operates properly and the front wheels turn firmly right and left.

10 PRACTICE LAP

If you have time to make a round before the race, run your car along the course. There is no need to rush it, but drive leisurely and important matter is to confirm that the car goes straight on the straight course. If not, adjust it with the trim lever of your trans-

11. RACE

Now is the time to start; countdown has begun: try not to be hasty. Be particularly careful not to make a premature start. The first curve right after the starting section is the place where collisions occur most frequently. So drive your car prudently. The point is to keep your coolness during the race. Vying with other cars and taking corners at great speed will most likely result in spinnyour own speed calmly. When you pass another car, try not to hit it from behind. Also, it is etiquette to give the right of way to a faste

car when being passed. During the race priority

should be given to completing the course. Try to finish all the laps designated without any accident.

12 AFTER THE BACE

You have run the complete distance and the race is over. Switch off your receiver and transmitter immediately and return the transmitter to the officials Although you may be anxious about the result, do not stand around the finish line, as you may be in the way of the officials. Get back to your seat and check your car, preparing for the

next competition. 13. ANNOUNCEMENT OF THE RESULTS AND COMMENDATION

CEREMONY After all the races are complete, the results are posted and the winners are honored. The winners should be praised by applause. Whether or not the competition is successful depends upon the attitude of everybody involved.

14. RETURNING OF TRANS-

Lastly, your transmitter is returned to you in exchange for a receipt. It is a serious breach of rules to pick up your transmitter from custody during the contest without permission. If you have to leave the site before the races are over, you must explain it to the official and get your transmitter returned by him. In such a case, you must keep the transmitter switched off until you are sufficiently away from the race site. TYPES OF RACES

• TIME BACE • LAP RACE

These three are typical types of races. In the time race, the winners are determined by the time required. In the point system race, points are given according to the make the final record to the lan race. the number laps a car can make in a certain time decides the winners. Of these, and the outcome is determined by the order

of arrival to the finish line. MANNERS IN DACE

Spirit of fair play is essential in any game. It is desirable to make a pleasant race event through the fair play spirit of all the

- *Transmitters are kept by the host organization without exception. *Transmitters in custody will not be taken out unless nassed by the officials *Yield the way when you are about to be passed by a faster car *When you hit another car, you should annionize. But do not ask for one after
- during a race. *After all the races are over, clean the site. No rubbish should be left behind.



THE CHALLANGE OF LE MANS



LONG DISTANCE AND

The Le Mans 24 hour race is done with racing sport cars, and the famous Spa-Francorchamps 24 hour race is done with touring type cars. A combination of driving ability and team-work of the pit crew are necessary for winning this type of race. Fuel (batteries); tire changes and the correction or replacement of broken parts is essential from the pit crew in the minimum time possible to remain competitive. A R/C long distance race should be conducted over a period of at least one hour, and the winner is the vehicle that completed the most laps during the period. Recharging batteries, assembling required spares and changes in the steering and gear ratios are only some of the things that might need to be accomplished during the race. Driver fatique can also be an important consideration during the race, and changes of drivers should be anticipated during a pit stop. The fastest car on the course is not necessarily going to be the winner. The car that maintains the best total average over the entire race is most likely going to win. Prior race planning and completely understanding the limitations of your vehicle, as to battery duration and speeds over the circuit can give you the edge for winning long distance races. The challenges of long distance racing are completely different from those of sprint races.



TOISE AND THE

● About "Speed" in long

In any long distance race, you cannot say for certain that the fastest vehicle is going to be the winner. We are all familiar with the tale of the "Tortoise and the Hare." The furtin was far slower than the rabbit but won the race by keeping a steady page throughout the course. Maximum acceleration and high too speed are not that necessary in long distance racing. If you have a very high performance car, tuned up to its capacity, and attempt to run a long distance race, you are likely to spin out often if you are initially concerned with leading the pack at the races outset. Fast acceleration and a high top speed utilize a large current flow from the battery, thereby reguiring more pit stops for battery changes. Long distance vehicles also require a greater degree of precision tuning, better maintenance, and durable parts, and perhaps a different gear ratio. The vehicle that makes the fewest pit stops will most likely be the winner.

LONG DISTANCE RACES Credibility & durability an

In full sized car racing, the machine used for long distance racing has less high speed performance than a racer for sprints. This is done so that the vehicle will last the entire race, and not become disabled prior to the finish. In radio controlled cars for long distance racing, the same is true. A car made from a kit properly will have this durability and be competitive during the entire race: however, if it is not built and assembled accurately, the chances of it surviving a race is slim. You must make sure that all screws and nuts are tightened firmly and where required, that liquid vent loosening. It is recommended that all electrical wire solices be soldered to ensure a good positive electrical contact throughout the race, and that the wiring is ing entangled in drive gears etc. Prior to the race, use new rubber bands and replace the doubled sided servo tape with fresh tape. A car that is lighter in weight will move faster; however, by lightening the chassis by drilling holes in it, or removing some bracing, you may find you are faster. but the car will not last the race because it is no longer durable. Credibility & durability are the keys to winning long distance.

Pit practice and n

The majority of pit work during the race will be battery changes. By saving time during these stops, you can greatly advance your standing in the race. It is very necessary that your crew practice removing the body. change batteries, replace the body and secure it on the chassis. The more this is practiced, the quicker they will be during the race. One second sawed in time is a gain of one second on the leader, and races are won and lost in less time than a second. During the race it is necessary to be calm during pit stops. If you are in too much of it is hurry vary could make mistakes.

races are won and lost in less time than a second. During the race it is necessary to be calm during pit stops. If you are in too the calm during pit stops, If you are in too off the calm of the pit stops. If you are in too off the calm of the pit stops in the calm of t

A powerful motor is not

A lame, powerful motor is a necessity in sprint type races where no battery changes are needed; however, the same does not hold true for long distance racing. Small motors which use little electric current are much better as they moulm fewer pit stops for battery changes. As an example, the 540 type and 380 type motors. are representative of motors used in radio control racino. The 540 type has a torque of 200gcm; RPM 11,000 and draws current at 6.25 amners. The 380 type on the other hand has a torque of 75ocm, RPM 12,800 and draws 2.9 amperes. This information shows that the 540 type motor produces more than double the power, but consumes also twice the current. A car using the 540 type motor will require many more pit stops for battery changes than one using the 380 type, and even though the car will be somewhat slower on the track, it will still be running while the former is in the pits for battery changes. Another point to consider, is that with the high current flow of



y, less complex curves. 12



more apt to cause trouble, and in any coultsion, the faster cris in normally damaged to a greater extent because of the higher interest of the state of the state of the state of the to drive during praces and missakes in driving are more likely to happen due to the special switch it is traveling. All of these special switch is in traveling. All of these when selecting a wehcle and motor for long distance action, A pood rule to for when working up a vertice for endurance tracks which have many fight contract fracks which have many fight contract forest straight runs, and use a higher performance engine with higher gearing for formance engine with higher gearing for

the larger motor, the speed controller is

NDS UPON TEAM

Organizing a racing team You can, of course be the driver, pit crew, and run an entire long distance race by yourself; however, you will not be overly successful very often doing this. Best results are obtained with a driver, mechanic for battery changes, repair and adjustment; time keeper who records and times the laps, and at learn manager who require more than one driver, so it is best iff

Team work gives the edge

Once the team is formed, the next step is to get it working together. Firstly, all members must know and practice the role they are to play The driver must run the car according to the team manager's instructions. It disrupts the team work when a driver struggles against other cars following his own selfish interests, or delays a pit stop etc. The mechanic is constantly preparing the batteries for changing, and keeping track of which are fresh and those in a discharged state. They look the same and in the flurried atmosphere of a race. more than one dead battery has been replaced by another dead one. He should be adept in quickly removing the car body for battery changing, and adjusting steering and changing tires etc. The time keeper plays an important role in-as-much as he records all of the fundamental data that the team manager uses to formulate his race strategy and tactics. At a minimum. he should record the number of laps run and the lapsed time from the beginning of the race. If possible, he should calculate the average lan time of the team's vehicle. time the pit stop and record what was done, plus keep track of who was driving and when a change of drivers occured. The team manager observes the progress of the other teams, and advises his driver as to pacing, pit stops etc. The team manager and time keeper should not be drivers in this race. During the second half of the race, when there is almost no difference between your car and the rivals team, it is the data provided by the time keeper that



will give the team manager the necessary information to guide his driver on to victory. It is the manager who is responsible



Periodic pit stop maintenance

The number of pit stops made must be reduced to the absolute minimum. If your only stops are for battery changes and/or driver change, then your race is progressing well. Keep in mind though, that it is also necessary to periodically oil bearings, and shafts Polish and oil speed controllers and to apply spray oil into motors and onto gears. This maintenance, although time consuming during a pit stop, must be done to prevent failure of a part due to lack of lubrication. Also look for any loosening screws and/or missing parts that may reguire maintenance during the next stop.

Trouble pit stops

As soon as a problem is noticed by the driver, he should pit the vehicle the next lap. To keep running the car with a problem will only create a worse problem, and perhaps one that can no longer be repaired during the race. After a bad collision or spin out, observe the vehicle for a lap or so. and if there is a problem pit it as soon as possible. During the latter stages of a race, it is difficult to judge if your vehicle is performing the same as at the beginning. You must compare your performance with your rivals, and if your vehicles running compares favorably with your opponent, keep formance is not as good as at the beginning. If you make a stop and discover that it will take too long to repair the fault, continue running the vehicle, rather than expending the repair time. The manager's judgement on this must be accepted.

 Pit tools and spare parts Keep the total number of tools in the pit to a minimum however make sure that you assemble the vehicle. A box wrench, for instance, is much better than an adjustable spanner. Needlenose pliers and tweezers are also required. If you take only one glue, the instant cvanoacrylate is recommended. Gummed tape, vinyl tape and soft iron wire are also very useful for making emergency repairs. Take along enough parts to completely rebuild the vehicle. Extra parts for the front-end and steering, and those parts that require assembly, should be assembled prior to the race, so that they can be installed as a unit, rather than part by part during a pit stop. Sponge type tires do not normally require replacement in races of two hours or under, Semi-pneumatic tires As for diplo tires, if the center rubber part of the tire is not firmly fastened, it may come off during the race. Wheels sometimes become broken, so even if you are using sponge tires, take along spare wheels on which you have mounted new tires, properly balanced and rounded off. Re prepared for anything that could likely occur. If you don't bring it, that's what will break during the race.

Battery changing

during races One very important, (perhaps the most important) part of racing, is how long your batteries will last during a given time. Ni-Cd batteries have the ability to deliver a constant even voltage and current supply to the motor, until the battery is almost exhausted. If you are familiar with the circuit you will be racing upon, you already know how many lans you can get from your bat-

tery on that circuit, however, if you are rac-The discharge characteristics of Tamiya Ni-Cd battery and UM2 dry cells Tamiya Ni-Od



ing on a different circuit, it will be quess work on your part to know how many laps racing, where many battery changes are reguired, you must have the ability to judge when a pit stop for battery changing is necessary. Normally, you will bring the car into the pits about two or three laps prior to battery exhaustion. Running the car until it stops from lack of power is not good for the battery, nor will you end up winning any races that way. Tires, driving technique. course length, number of laps required course condition, type of motor, all play a part in how long a battery will last. Be on pits after you have run the battery down to

its safe limit, by measuring the time or laps

run. Make sure that your battery supply for

the race is sufficient for the entire race, to

include two or three extra batteries, for pro-

tection in case of an accident on the track. or battery malfunction. The smooth, steady driver, who makes the required pit stops on time, is the driver who will win endurance racing.

Radio control battery life

Normally, you will not require a fresh receiver or transmitter battery during a race that is not longer than one hour, if you channed Ni-Cris Note however that the more servos you use, the more the receiver battery is used. Whatever equipment you use, you must be familiar with the nominal life expectancy of the batteries, and if there is a possibility of the race lasting longer than expected prepare extra batteries beforehand, just in case they are needed at a pit stop TECHNIQUES FOR WIN-

NING LONG DISTANCE

Endurance or long distance races are very much like human distance racing. To win, you must establish and keep a steady pace throughout the race, avoiding useless deadheats with other rivals at all times. Keep clear of trouble on the track and run your car at a steady even pace.

Start

You do not have to "Jack Rabbit" start Take it easy and run carefully at the beginning, especially at the first corner, where accidents often occur. Enter the corner high. even if you are left behind at this curve. Ac cidents at the beginning of the race often leave the driver irritated and confused, and the original plan of paging is lost. For the first two or three laps be very deliberate in your driving. You will start to relax, learn the track and how the others are pacing become upset and dash to catch up. Keep the pace and drive smoothly.

How to pass and get

ahead of rivals Success in long distance racing usually comes from not being in the lead for most of the race. When you are the front runner, you are always concerned about those who maintain enough distance in the lead over your rivals, it is better to let one or two pass you, than constantly worrying about them. You can then use the leader as a pace setter for you, and when the time comes for you to pass, do it right after a corner that is followed by a long straightaway. Even if your car seems to be slower than others in the race, you still have a good chance of winning Remember that the faster a car runs, the more battery it consumes, and the faster cars will have to make more pit stops. This is your chance to catch up and pass them. If you can just manage to keep your own pace, throughout the race, you have a good chance for the winner's trophy.



Relax when

cornering During the endurance races, take the mid

dle or high comer, rather than at the track inside edge. This is where many accidents from their last spin out will be fighting for that inside lane, and most likely spin out again. If you are there, you could be knock ed out in the accident. Stay high in the corner and relax except for that time when you need the extra speed and dash for win ning the race. Relax and win!

RECORD THE BACE In long distance races, it is advisable to

keep a record of the race. Later, you will be able to review it with your team mates and determine where time was lost. This is a very useful and positive approach to improve and strengthen your team for other long races.

Pit records This is the record of all pit stops of your

car. Which laps the stops occurred, how long the stop was for. The reasons for the each stop. Perhaps you only changed drivers and batteries, or perhaps changed tires due to new track conditions (rain; oil on track etc.). Whatever the reason, this information will assist you in making a better overall plan for the next long distance race.

Race progress records This is a record of the progress of the race,

lan by lan. It will consist of the lan times. driver's name and any other information deemed necessary during the actual running of the car in the race. This information will provide you with planning data for certain conditions; number of laps expected during an hour of driving time; and number of pit stops expected.

Lap record listing

This is the data which the promoter of the race records. The number of laps of each team is recorded every 5 minutes. From this record, the pace of each team is determined, and the progress of the race. He will know which car is ahead and also when another car takes the lead from a rival



It is a thrill to participate in a race; however it is a more significant experience to organize a contest. A competition requires many people: timekeepers, course committee members, etc. in small races, such as those organized by hobby stores, players, often serve concurrently as officials. It will be anpreciated if you can offer a hand as an official. It is not only welcomed by an organization, but it is also rewarding to yourself. The experience of taking part in a race meet as an official will surely help you with organizing another event. Moreover, it will

be of much benefit to you when you particinate in a contest as racer 1. TYPES OF RACES

There are many types of races: series, single ones, and others. It is a common pur-

pose to compete with fellow racers and to develop skills. The more races you participate in, the better results you can expect. Many races are organized in a series. to compete throughout the year in order to single out a champion

OPOINT SYSTEM SERIES Points are given to contestants in proportion to records achieved at each individual race. The winner, 2nd, 3rd places and so forth are determined respectively by the total points accumulated in the series.

• REPECHAGE SERIES

(PRELIMINARY) The big drawback of the point system series is that it is unfavorable to participants who join late. The repechage series has been organized for eliminating this drawback. For example, minor races are held every month to choose a champion of the month. The annual event is conducted to determine a champion of the year. Anyone who has become a champion of the month is aliminated from the following monthly netent person to the annual final race) is chosen every month, and contestants from the middle will not be put at a disadvantage. At the same time, this system will give

an apportunity to low accords to win a

monthly race. Of course the minor races.

can be held every week instead of every

month and the grand championship can be

held semi-annually. Though two types of series have just been introduced, the vital point of making a race successful lies in a winning as widely as possible among all contestants

Open to anybody Some limitation by any

These are two typical systems. It is usually common that employees or members of the host organization are not eligible, but they may be admitted under the condition that they are eliminated from obtaining

awards and ranking.

3. ANNOUNCEMENT OF A It can be announced through posters.

Handouts are also good media to publicize the competition. Essential factors such as when, where, qualification, way of grouping, kinds of cars, type of race and method of determining ranking should be described if the race is the series system an-

events is desirable

nouncement of dates of the following Entry forms should be ready at the registration desk. Columns for name, address, age. occupation, entry class, frequency of radio be provided along with entrance requirements. It is recommended for a host organ-

STORE GRAND PRIX ENTRY CARD

iame Iddress	
ige Brade)	Occupation

Car Number

	Band	1	2	3	4	5	6	A	В	
Store 1 S t	Store Grand Prix Entry Card									
	1 5 t	2 n d			3 r d		4 t			
	5 t	6 t		7			8 t			

ization to make an entry register book, as it will be useful for reference. With a series race, it is important to keep records of contestants. Fotry forms are made in dunlicate: one for participant, the other for the organization to make a ledger.

5. GROUPING OF

• Group by age · Group by skill and experience

The above two methods are good ways to form groups. There can be a beginner and an advanced class, if sorting is carefully done. Top ranking contestants in the hevanced class in the next race.

6 GROUDING OF MODELS By batteries · By motors

Rasinally there are these two classes. You could classify by types of cars or vehicles or by scale, but orouping by battery type or motor type is probably more satisfactory because the demands of different types of track will alter the battery or motor requirement. On a straight course

where cars can race at their maximum result between cars with dry cells and those with nickel cadmium batteries, or amongst cars with nickel cadmium batteries of different voltage. On a track where a lot of corners call for deceleration it is imperative to have separate classes for cars with small 380 motors, bigger and more powerful 540 type motors, and race oriented. high performance motors like Tambra Technigold and Dynatech Motors

 Modified car class As a modeller enriches his experience

through numerous races and grows famili iar with radio control, he is urged to modi fy and increase the performance of his car. Increasing performance may be end lessly sought after. However, considering the cost of modifications and the finesse required, only a few people may be able to achieve this. It is practical to organise a class of modified cars with some limits so that those who do not have the technical knowledge or the necessary finances to carry out major modifications, may participate in the race.

• Speed course ● Speed course

■ Sachnical course

A speed course has a rather long strainte away where it is easy to nick up speed. Performance of a car is a key factor to win or lose a race. So with a speed course, a distinction of cars driven by dry hattery from nickel cadmium ones and remodelled car classes are necessary. A technical course consists of a lot of curves, and the driving techniques are more important than capability of a car. With the course, therefore sorting of classes by car types is not neces sarily required. Since the Tamiya cars can go backward, it might be interesting to a dopt parking and reverse going courses.

• Car check Impounding transmitters

Ascertain who the participants are with the entry form. Check if the car is qualified under the requirements of the particular racing class. At the registration desk, impound the transmitters of all the contestants. Of course, return them to assigned racers just before the races begin. As soon as the race is over, the transmitters should be impounded again. In other words, all the transmitters of the contestant are to be under custody of the host organization all the time during the event, except for those which are being used for a race. This is done at any radio control racing gathering . The transmitters in custody had better have attached a contest number and be kept in a grouping of frequencies.

Radio frequency control

See

 ● Race administration In a radio controlled car race cars using the same frequency cannot compete at a

time. Reversely speaking, only as many cars as there are different frequencies can race simultaneously. However, to avoid interference, cars with every other frequency should be arranged to compete

Mr. 0 2 M. E 3 4 6 Mr. 5 Mr. U 1st heat (6 races)

- Aug 2 3 1 Mr. A Mr. 8 Mr. C 2 3 Mr. 0 Mr. 16 4 80. 1 . 6 Mr. P Mr. 0 A

2nd heat (6 races) Per 7 8 10 11 12 . 2 . 3 80. K Mr. J 5 W- 8 . . . A

When there are eight contestants, a race is formed with four people to participate. making two races. Races are done reneatedly for each combination (each race called "heat" or "round"). Points of each heat are to be summed up to determine the

Mr. X

R Mr. V

OKINDS OF RACES

 Point system race ● Time race

 Round race These three are typical kinds of races. And it is common through these three that the combination of the members should be changed so that any participant has an opportunity to compate with as many other

contestants as possible.

POINT SYSTEM RACE

Points are given to each heat. The noints . Depending upon combination of entrants to

a heat, sometimes only 2 or 3 people can contend. Even in such a case, the points of the first place are awarded. . When the total points of all the heats tie the

score a playoff will be held. When contestants using the same frequency should end in a draw, the winner is chosen by comparing the rankings of each heat, or else they are made to vie for superiority by running one by one for time.

OTIME RACE

Sometimes the point system is used together with time to get the result more distinctly.

OLAP RACE

One who makes the most number of lans on the course in a given time is the winner. This method is often employed for long distance endurance contests. A notable common feature through point system, time classified under a frequency to use. Because participants using the same frequency will be never contend at the same time under any circumstances, the final ranking is not necessarily reflected with their real ability of controlling models. This is something which cannot be helped so long as the frequencies are restricted to a limited number. However, the problem can be solved to some extent by arranging races. in a series form or assorted with the time race system.

10. PENALTY POINTS

A participant should be penalized when he conducts himself against the spirit of fair play or against the smooth progress of a contest. The punishment is disqualification and then imposition of a cut in marks or additional penalty time

. It is usual that interference to other cars and remodeling exceeding the limit should be liable to disqualification * A breakaway is subject to demerit mark. The penalty system should be constituted from the standard of annoyance to other participants or injustice among the entrants

11. TROUBLE

When a model gets out of order in the midst of a race and is unable to proceed or out of control, all cars in the race should Restarting

In case the cars go out of control by radio interference, or the race is obstructed by

spectators or somebody else, restarting

@ Datimenant In case a model cannot proceed in the race

due to insufficient previous check up or because of an accident while racing the said car only must retire from the race.

12. ACCOMMODATION Ample consideration is desired to be given to conveniences and accommodations in

an exciting atmosphere to the race. @ Start flag Generally a national flag or a flag of the host organization is in use. ♠ Finish flag (checkered flag)

A checker flag of black and white is waved to the winner's car just before and when crossing the finish line.

To help the race proceedings a score board is desirable to be installed for announcing the records of each heat and ranking to the public. Control stand

A stand is very convenient to install so that the drivers can control in better view of the course and the cars while racing. @ Props in the course layout A bridge made of a tire or advertisement sion boards of companies which can be seen along a real racing track, and miniature guard rails used as pylons in the course will enliven the race.







1. POINTS IN DESIGNING A RACING CIRCUIT

Building a racing course, even a simple one, lets you enjoy it far better than running a car in a large open space freely. You can make one very easily, i.e. by drawing lines with chalk or using empty bottles for pylons (when using a space of someone's possession, like a parking lot; of course. nermission should be acquired beforehand). To make races more fun, some knowledge of courses are required.

2. A TRACK BEFITTING You cannot expect a thrill of excitement in

running cars along a too wide circuit. In a too narrow track, you cannot enjoy speedy driving. The maximum speed of 1/12 electric R/C cars is around 30 km/h and the width of the car body is about 20 centimeters. Based upon these figures, the following designing data will be introduced: *The length of a course is 100-150 meters.

*The width of the course is 3-4 meters.

The maximum speed of 30 km/h comes to a little over 8 meters per second. Taking tue slow down at corners into consideration, the car will make a round of a 150 meters long circuit in about 15 seconds. In the Tamiya Circuit, a round of the longest course out of the possible selections

measures about 140 meters. A race is held



by making three rounds. The average time required is approximately one minute. This is a rather long time to a racer, as he has to apply all his energies in the control from the size (breadth) of the models. The

The width of the road should be desinged

1/12 cars are 20 centimeters wide. So having 10 centimeters in between cars. then 2.5 meters of width is required for 8 racing cars. If a way should be established in that all cars do not start from the starting line in a row a narrower width of the course would be permissible. But for avoiding collisions and bumping while passing each other, the breadth of over 2 meters 50 centimeters is desirable. The Tamiya Circuit is 4 meters wide (sometimes 3 meters) but still it does not look too broad. There should be at least one portion of a straight line in a course where cars are allowed to run at their maximum speed. The longest straight in the Tamiya Circuit is 37 meters. long, 1/12 electric cars can cover this length in 5 seconds or so. Here, on this straight, the driver can take a breather. A longer straight course, depending on cars' ability, may be desirable. A drag race can be held in a straight of over 40 meters to contend for 0-400 meter pick-up perfor-

mance (converted in 1/12, it should be about 33.4 meters.) 3. TRACK CHARACTERIS-TICS ARE DETERMINED

BY CURVES

Circuits are roughly classified in two groups: a high speed course where velocity is important, and a low speed course where control techniques are more important. The features of a track are formed with the number and characteristics of many curves. An ideal circuit conceivable is a mixture of high and low speed courses for 1/12 electric model cars which boast of excellent maneuverability due to the differential gear device equipped.

OKIND AND CHARACTERISTICS OF CURVES

High speed curve. Medium speed curve. Low speed curve High speed curve - Cars can pass through at high m speed curve - Some slow down is called for Many car will be spinning and

Low speed curve - Hair pin curve (prudent running

negotiating a curve without losing



OCCUPIES CURVE SUCCESSION OF

Try to anticipate the course ahead. Watch for places to pass skidding opp ●Wider outside curve ● Wider inside curve Curves can be divided in three groups in terms of passing speed; High speed curve which a car can go through with almost no deceleration, medium speed curve where some slow down is required, and low speed

curve. And in terms of layout, a simple curve is one built with a single radius, and a complex curve consists of multiple radii. Straights between curves are also influential. With all these features being incorporated, quite a challenging circuit can be made with curves of different characteris-Please refer to the illustration of the Tamiya Circuit and the drawing for the individual feature of curves. Also,

note the point of vertexes are made not too sharp. According to the data gathered at the Tamiya Circuit, cars are act to deviate from the course towards the outside at high speed curves and inside at low speed curves. The road surface of the curves have been modified accordingly.

4. FROM A DRIVER'S VIEW The hinnest difference between the real

car and the radio controlled model is of course, the position of drivers. Hence, the following hints have been brought about:

16

should be a length of

The farther away from the driver, the narrower the course looks because of parallax. It could be some problem to drivers. To compensate for this, this particular portion of a circuit should be widened. In case of the Tamiya Circuit, the opposite side of the track to the driver's stand is 4 meters wide. One meter wider than the near side. ed to design a course with complex curves where meticulous controlling is required a distance away from the driver. Some bridges and gates on the circuit are very useful auxiliary articles to make the circuit lifelike; however, again, attention must be paid not to block the view of curves from the driver's sight

TAMIYA CIRCUIT

5. TO MAKE A RACE MORE **ENJOYABLE**

Most of the electric cars have the same or similar performance, so there is a likelibood that they could collide if there is a sharp curve right after the start of a race. Therefore, it is recommended that some length of straight running be available just after starting. It is not necessary to have the circuit at one level. On the contrary, some undulation and a leaping slope or two may be useful to add to the course more variety and making the race more eniovable unless these objects would hide the car from their vision.

6. TRACK SURFACE AND COLIRSE SIDE

* The pavement of the track need not be very smooth.

*Lawn is ideal for course side. Pavement of simple surfacing asphalt is adequate without a firm foundation. Or a Sunday chore by the club members to apy concrete surface may suffice for the purpose. Some uneverness and slope will not be a cause of trouble, but drainage should be planned carefully. Shortly mowed lawn on the side space of

ce palantec carefully control to side space or the course is clear when considering deviation of cars from the track. However, it would call to firm and care to grow. On the Taminya Circuit, artificial runs conduction of the course of the c

viated to get back to the course with ease. When the space between courses is very narrow, some device may be needed to keep a car from jumping into the next course.

7. DRIVERS CONTROL
STAND AND OTHER

ACCOMMODATION

The larger a circuit is, the tailer the control stand must be. The Tamiya Circuit has a control stand of about 2 meters high However, when a stand is too high, it would be inconvenient to step up and down. Sometimes a hand rail, for safety's sale may be

Besides bridges and gates on the circuit, a signal light for starting, a control tower, sign boards of sponsors, and things like that are desirable so as to boost up the atmosphere; hints of such auxiliary props can be obtained in car and racing maga-

should be any rise and fall between surface levels, in order to allow a car that de-VARIOUS PLANS OF CIRCUIT LAYOUT



1 LARGE CIRCUIT



SQUARE





Bank







electric car kit may produce much diistics in accordance with a way it is assembled and adjusted; for example, some cars are easy to control and some are not

1. FUNDAMENTAL REQUIRE-

MENT IS THAT THE CAR Even with a real automobile, moving in a

straight line is the essential condition. A model should be adjusted so that it takes in a beeline for 5 meters or so without touching the steering wheel. A car which does not go straight cannot be controlled easily. Note the following points: A car with distorted chassis would



chassis so that the four wheels should touch the ground evenly. Particularly after collision, look into it carefully @ If any wheel should not rotate smooth ly, the car would turn in the direction of that wheel. Assemble a car with care so all

wheels revolve evenly. This is related to car's running capability. f a front axle is not set parallel to the rear axle, the car will steer crooked.

With a bent rear axle the car will keep



A When a wheel is not secured firmly with the nut, the car may be going in a zigzag way. Tighten the nut to keep the



wheel in position in such a way that there is no play between the wheel and the axle. but still allows the wheel to turn smoothly. The steering servo and servo horn

should be arranged so that the front wheel will head forward right and the attitude of the servo horn is parallel to the front MADCAP (TOP VIEW)



+IT GOES STRAIGHT BUT TURNS UNEVENLY RIGHT



+ DOES NOT GO STRAIGHT >-



18





wheels (some cars requiring a right angle), when the steering servo (consequently the steering stick and trim lever) is in the neutral position. When this arrangement is not right, the car would not go straight or it will change its course



unevenly to right and left. Being installed with a screw, servo horns can be read-Try to mount radio control units and batteries into a car, balancing the car

@ Be careful that tires and steering linkage will not rub against the body. Lastly, have a test it with the trim lever on the transmitter With the trim lever, you can do the fine adjustment of servo movement, having the same effect of shifting servo position.





(HINT) A car with long wheelbase in relation to tread has stability and tendency of going straight.



A car which goes straight is easy to control in principle. Such a car should have no peculiar action when taking corners. Cars with a peculiar way when turning can be

corrected in the following ways. The direction of front wheels are controlled by the movement of a servo. In case a servo is not secured in position firmly. the car tends to be unstable having a littering or not responding to the control properly, or turning unevenly right and left. When dual-sided adhesive tape is CHOW TO APPLY DOUBLE Double Sided



Double sided ing sure it's not lives. used for mounting a servo, wipe the surface of the servo with cloth dampened with thinner may dissolve servo cases.) INSTALLATION OF SERVO HORN ...

BAD EXAMPLE - large -

Travel of servo horn between B & C is almost



When servo horn is installed incorrectly

When a differential gear does not work properly (the same state as if without a differential gear), the car is apt to make a big turn or take corners awkwardly. Check it by holding one wheel firmly and turn the other wheel; smooth rotation indicates the differential gear is in good condition. When it does not, try to give some play in the gear meshing.

CHECKING DIFFERENTIAL GEAR-



- WHY DIFFERENTIAL IS USED -



orn, or wheels are in contact with something like the car body preventing right



 Lubricate the king pin of the front wheels. Steering should operate smoothly (HINT) Steerage (degree of changing direction of front wheels) can be varied by shifting the connecting point of the servo rod. It is recommended for a beginner to

select small steerage. • Small 0

3. FOR SPEEDING UP (TUNE UP) Most electric car kits are produced to come out with similar performance. In practice, however, the models assembled will show varied ability. The reason why some cars do not run faster than others are, in most cases, that they have additional friction around the rotating parts: in other words, they have a rotating section which, either partly or all, does not revolve smoothly. The following are the points to take care of, needless to say applying oil or grease to the places re-

@ Furnish some play in the meshing between the pinion gear of the motor and the differential gear. Too tight meshing degrades the rotation and hampers the speed: on the contrary, too loose meshing would damage the gear teeth.



@ Clean the surfaces of gear teeth with a used toothbrush or scrape them with the dust and dirt which would kill the smooth rotation.



A chipped or deformed gear tooth will diminish the rotation. Particularly a brass near is easily warned: in such a case, reshape it with a file carefully The collar should not be located against. the bearing too tightly. Secure them in

that the shaft would move slightly right and left

A bend in the rear shaft will be a cause of unstableness of the car, especially when running at high speed since it may make the car slower compared to other cars. The bend can be found out easily by rolling the shaft slowly on a flat surface. Flat square

When a tire is not glued firmly or the wheel hub is warped, the effect is the same as if the axle is bent; the car cannot go fast. - Instant cement

Semi-pneumatic tire Fit tim to wheel, and

ponge tires should also be firmly glued to the wheel using software carriers included in kit. Orniting this will



looked. Do it without fail. Poor rotation on the front wheels influences the car's speed more unfavorably than you may think.

think.

Improper toe-in and toe-out adjustments are resistant to the car. The model car runs well without toe-in and toe-out or with a few degrees of either.





Alteration of toe-in and toe-out can be made by altering the ball adjusting joints. Adjust it as illustrated below. The 5000 Ball Adjusting Joint Set may be fitted on



DAILY MAINTENANCE



Dally up-keep of your cars is important for maintaining performance. This will help you to find any possible defect. Without daily care the capabilities of acceleration and maximum speed of your models can deteriorate. Keep your cars in the best condition possible at all times.

CARE AFTER RUNNING
 After running your model be sure to clean it and carry out any necessary repairs ready for the next time you wish to run

*ATTENDING TO CONTROL MECHANISMS
The radio control units and switches will
be a control units and switches will
be a control units and the switches
must be cleaned in order to avoid por
contact. Any component damaged or out
of position must be replaced or repositioned. Dry cells may be in need of sechange. Also check the batteries of the
control units. As a general guide,
the receiver batteries are exhausted
the receiver batteries are exhausted
adoptant batteries tend to be a cause of

* DIRTY COMPONENTS AROUND THE

many breakdowns.

After a day's activity, all parts and sections around the chassis will be in a dirty condition. Look particularly at the moving parts, any foreign objects in the bearings influence the rotation of the wheels. For increasible places use Tamiya Szerg VIII, which has a detergent effect and is very useful for cleaning. Chack if any nut or sushed for cleaning. Chack if any nut or See if the rear axis is bent hall sections.



Radio controlled racing cars are not only for running, but are also fine scale models. It is certainly not recommended to run the cars without a windscreen, with a door broken, or with a big hole on the body or any similar damage. Always keep your model in the best condition possible, thems you will probably need for repaible, thems you will probably need for repaible, are plastic sheet and different kinds of glue. Synthetic rubber cement and instant glue are useful, as well as plastic olse.

2. TO KEEP YOUR CAR AT PEAK PERFORMANCE

PEAK PERFORMANCE
Parts will wear out or become broken
after periods of high speed running and
use. Replace any damaged parts and keep
your model constantly rejuvenated.

MIAINTENANCE OF ELECTRIC SYSTEMS

*REPAIRING ELECTRIC WIRE
The electric wire is able to withstand to some degrees of moisture and stretching. Ac-

The electric wire is able to withstand to some degrees of missiture and stretching. Accidental contact of exposed wires will result in a short-cliental contact of exposed wires will result in a short-cliental, which may demage the battery, motor or switch; sometimes causing components to burn µ. A wire out of place may jam tito a shart of the cart. When the wiring of radio control units with the work of the control with the control with the wiring of a car rubs against a when the wiring of a car rubs against a consecue or other parts with results in a

noise being emitted, the radio control unit Salte dose a cost which is not of place.

Cover with viry! tape any part of the cool where insulation is coming off.

will be disturbed and will not operate correctly. If the insulation should come off any part of the exposed electric cord, it must be mended immediately and thoroughly. Any joins in the wining about to break should be rejoined firmly, preferably by soldering. If a radio control unit or antenna should fall to work correctly, it must be repaired by a competent radio re-

*POOR CONTACT OF WIRING Since it draws a lot of current, the speed control switch when it sparks will scorch

control switch when it sparks will scored in the contact points. This scorning will, after a while, cause poor contact. The sportment of the connectors and welches points of the connectors and welches electricity to flow with less resistance, may be repaired by a screw driver, refer to may be repaired by a screw driver, refer to see the connectors may be repaired by a screw driver, refer to be carefully politished with very fine sample. Media Connection and the carefully politished with very fine sampler. Media Connect surfaces were admitted to the carefully politished with very fine sampler. Media Connect surfaces were admitted to the carefully politished with very fine sampler. Media Connection structures were admitted to the connection of the connection o

some period of operation

The state of the s

MAINTENANCE OF
MECHANISM AND CHASSIS
*LOOSENED INSTALLATION OF RADIO
CONTROLLED UNITS

The adhesive power of double-sided tape is much reduced after one application. If the tape is reused to install servos or receivers the units will be moved out of position due to accidents or vibrations. Loose bolts and nuts fixing the servo bands and servo travs may result in inaccurate control of the car, For installing steering servo and speed control servo ed bolts and nuts. Keep the double-sided adhesive tape in a cool and dry place. otherwise its adhesive properties may deteriorate. On the other hand, if the tape applied will not come off easily, wipe with The same cloth moistened with benzine assures strong adhesion if used to clean the surfaces of objects, i.e. servos and servo mounts, before applying the new



*LOOSENING AND DETERIORATION OF BOLTS AND NUTS Nuts and bolts are indispensable assem-

Nots and botts are indispensable assembly parts and can become damaged during the property of the property of

1/10 LOTUS HONDA 99T







with the running performance of your car. within the shock absorbers results in stiff piston rod, replace it at once with a straight

*GREASE-UP POINTS

rear axles where parts rub against each other to reduce friction and abrasion. After races parts, it is important, especially after races in the rain or through puddles, to look for signs also allows proper adjustment to the steering and gives smooth operation. Lubricate the influential in giving effective power transmission. The Tamiya Soray Oil is very useful for

taking care of these sections.

+ MESHING OF GEARS motor power and they are subject to wear. Any dirt and dust between the gear teeth will act sionally, cears may be broken by small pebrun much better if regular attention is given not use new gears for races until run in.



WHEN THE CAR FAILS TO MOVE See if the switching servo operates properly If not, you may have neglected to switch on

TROUBLE

SHOOTING

either or both your transmitter and receiver, or failed to install batteries. Also, the wiring between the receiver switch and the receiver disconnected. Inoperative radio control units can be detected by replacing them with

@ Remove the pushrod between the speed may be wrong and expessive resistance may hinder the movement of the servo. Something may also be in the way of the movement of the speed control switch. Please also refer to (2-Milin "When the Car Does Not Gain Speed"

When the switching servo and the speed does not rotate, see if the batteries are fresh

A Remove the motor from the nearboy and see if it will run. If it does, the meshing of the cears may be too tight, or the rear axle or the shaft and carefully polish the seized part with



When the motor is removed from the near contacts in the battery box, switch, or in the connectors are possible. Check the wiring first. battery box, switch and connectors. If the ponent pressed on may have a poor contact

bad contact after repeated use. Crimp the tubular contact point using the tip of a screwdriver to make the contacts slip in



become damaged when dropped, dipped into water, short circuited, or connected to too many batteries.

2. WHEN THE CAR DOES NOT GAIN SPEED

Make sure the speed control switch speed only in the reverse position, or when manipulated by hand with the servo rod disconnected, the neutral position of the servo ment, if it does not shift into the reverse speed but works correctly in the forward setting. see if the servo and the servo rod are install switch blade can go all the way to the maximum speed end. When the adjustment is incorrect and the switch blade does not move all the way to the end or goes over it, problems

may arise. 3 STEP FORWARD 2 STEP REVERSE



. Make sure that the speed control plate is parallel with the speed control servo, or it will result in poor contact. Check neutral posi-



21

3 STEP FORWARD AND REVERSE SPEED

2nd Low hom so that switch blade moves to the place shown when transmitter stick is pushed up to full.



. The hole position on the senio hom determines the arm * Adjust the height of servo horn and switch plate as even as possible. Bad contact occur in top speed position, if the difference

VADIABLE DESISTANCE SPEED CONTROLLER . Adjust stop position using transmitter trim lever.

When the speed controller and servo hom are not aligned as . Long running at middle and low speed may burn out the speed controller. Adjust speed control arm to reach top speed position.



Move arm in the direc Loosen 2mm nut

@See if something is in the way of the servo horn or the speed control arm which can block their proper movement. When car does not run with the speed controller arm in too speed, check contact by pressing lightly on the speed controller arm. If the car runs upon pressing, this indicates faulty contact within the speed controller Clean all dirt and debris from contact and reapply switch lubricant. Also check to see whether contact points are worn and change

if necessary. A Check to see if the gear meshing or the shaft are too tight. Make sure the wheels rotate smoothly. Be sure to lubricate shaft and

gear box

*ADJUSTMENT OF SWITCH >





. The adjustment of the blade should be made

referring to the assembly instruction sketch

Resistors are utilized in all speed controllers to vary the amount of voltage passing to the ed. Resistors impede the flow of current from the battery to the motor and the excess current is bled off in the form of heat. At full speed, the resistor is not impeding any cur-



When "Throttling" back, to slow down, or run at a lower speed, the fixed resistors will get very hot in the step type speed controllers. The variable control speed resistor (Wire wound) that use a sliding blade, are electrically altering the length of the resistor wire, so this type of speed control does not heat up like the others. When driving in the low or 2nd speed the ceramic resistors will get very hot,



O Does the steering servo operate properly? If not, the wiring from the receiver to the steering servo may be disconnected Remove the steering serve If it operates nonmally, the servo born or the servo rod may be rubbing against something. Also, it is possi ble that the king pins of the front wheels do

not move smoothly. When the car does not take corners well. refer to 1 and 2 on the page of "Building a High Performance Car*

DES NOT STO

 Do the speed control switch and the switching servo stop at the neutral position? If not, adjust it with the trim lever on the transmitter. After the adjustment, if the car runs at high speed even though the switch is in the stop position, the switching servo or the servo rod may be mounted improperly. Correct them referring to (2 - 0) in "When the Car Does Not @ Evnessive play in the connection between the switching senso and the speed control

switch may cause the switch to fail to return

to the stop position even when the servo is at

O If the batteries of the transmitter or receiver are low, the radio control will not operate.

Replace with new batteries.



Are the antennas of the transmitter and receiver OK? The following actions make the reception of radio signals poor; shortening the receiver antenna wire, winding the wire around the antenna tube, leaving the wire inside the model car, or removing the insulation of the



Make sure that metal parts of the car do not rub together under vibration. Rubbing between metal parts will sometimes generate radio noise which disturbs radio control. O Hold the transmitter away from the car with the control stick in the neutral position. If the servos are olitchino, it is most likely caused by radio interference



VING CARE

OFF ROAD

CAN CAUSE MISHAPS AND

PROBLEMS Even though you own an off-road vehicle you must select your driving areas with care to keep your vehicle in good condition. Inconsiderate driving will cause trouble

and possible damage to your car. 1. UNSUITABLE DRIVING

ODRY RIVER RED A dry river bed where many large rocks are found is perhaps the worst place for driving an off roader. In 1/10 scale, even a stone with a 10cm dia is the same as a 1 meter dia boulder in real life. Driving against these objects is like intentionally destroy-



GRASSLAND

Grasslands with tall grass and stems are bad for buggles because the grass can become entangled in the shafts and universal joints which cause an unnecessary load on the motor which can



2. SURFACE THAT REQUIRE SPECIAL HANDLING

 ASPHALT AND LAWNS Highspeed cornering on concrete, asphalt or smooth lawns will cause the vehicle to roll. Slow down a little when cornering on



3. DIFFICULT SURFACES GRAVEL AND DRY SAND These surfaces offer considerable resistance to your vehicle. There is a bur-

den on the motor and it will use much more current. The vehicle will not move as fast without moving the car.



4 JUMPS

Dynamic lumping is a part of off road driving: however, you can damage your car if you do it recklessly. A jump must be done so that the rear wheels land first with the vehicle level. In order for it to be in a level/slightly nose high attitude, you must leave the ramp squarely and not enter it





Upper surface of jump ramp is level













































land off balance. Your jumping ramp can be up to 20cm in height for safe, smooth







You may sometimes run into a puddle or two when running off-road. Radio control unit. motor, speed controller, and batteries are very sensitive to moisture. Avoid running into standing water and heavy rain. A splash of





6 MAINTAINING OFF ROAD Since off road cars and buggles are designed



to nun mostly on dirt, and often are nun on

these surfaces, dust is a major problem com-

pared to on-road-going cars. Always complete-

ly clean your car after running it. Dust can be

easily removed using brushes with stiff bristles. If the car was drove through loose ground or nuddle ending up with mud all over the car

wice off mud from easy-to-reach areas using

tissue papers or rap and let the rest of the dirt

dry off. When completely dried, mud will come off easily by brushing and chipping off using

screwdrivers. For nasty mud clogs remove

wheel suspension etc for a thorough clean

up. Remove all mechanics such as servos. receiver, speed controller, and motor when

washing with water to prevent water getting in-

to the mechanics. After washing completely

wipe off moisture and thoroughly dry to pre-

vent any rust, and reapply oil and grease in

gear box, shafts, bearing, and all moving parts.



Add much gravel here. (A), (B) Points
Put a lot of gravel on the inside of High speed, full counter steering course. . The most difficult driving areas OVAL DIRT COURSE An oval dirt course can be set up on school grounds



DRIVING IN RAIN

It is recommended to refrain from running your car in rain because the radio control mechanism is liable to be affected by water. However, races may be held in drizzle. It is necessary to have some basic knowledge of driving in the rain.



DAIN

Any well race track is very slippery, so cars may spin even when they accelerate at the start. Read the description of driving on support surfaces on page 8 and river your slippery surfaces on page 8 and river your deceleration and sudden steering are about in comerning, keep the steering about in comerning, keep the steering about in comerning, keep the steering bell of the steering racius is single. When there are puddles on the carcioustes, swold them even if your can has to through deep water, the wide Conder, the subsciously support and the solid product of the support of the sup

The radio control mechanism, particulars, particulars, the receiver and servois, contains precipion electric circuits carrying weak eleccition electric circuits carrying weak electronic properties of the receiver and the receiver as abort circuit which often causes damage to an control the car. If a wet electric circuit is kept electrified, its line wiring begins to control the car. If a wet electric circuit is kept electrified, its line wiring begins to some time later. Such a circuit may be and may be broken even by a slight shock some time later. Such a circuit may be control mechanism must be made waterproof. If the wealther forecasts aim on the day of course, it is receively to make the add con-

It is rare for the radio control mechanism to get wet directly by raindrops because it is contained in the car body. Pay attention to water splashed by the front and rear wheels and water entering the car body through the chassis. Openings in the chassis, such as holes bored to reduce weight, should be covered up with virryl tapp or similar. Another means for pre-

venting spray from entering the car body is to fix screens of toughened polystyrene sheet or aluminium plate to the chassis parts just in front of, behind, and inside

The receiver in the radio control mechanism is most likely to be affected by water. To make it waterproof, wrap it in a

Make the receiver and before waterproof.

To a view forely with plant band or notice band.

vinyl bag, the mouth of which is firmly closed by means of a mylon band, as shown in the illustration. It is advisable to apply vinyl tape or similar to the joints of connectors and casing. It is difficult to put servos into vinyl bags because they have moving parts. However, at least their lead wire holes should be filled with synthetic rubber adhesive. The watercroof-



mechanism and traction motor is also important. Put the connectors into a viryl bag and close it by means of robber of the control of the con



NOTE: Vinyl bags, though cheap and readily available, are prone to tearing easily and will not offer permanent protection such as the Tamiya nubber bags will.

S. MANY EXAMPLE AFTER RUNNING
On a rainy day, the car gets very wet and dirty, and it is almost impossible to prevent water from entering the car. If it is left as it is, the chassis, etc., may rust and the radio control mechanism may develop unexpected trouble. After using the car in rain, be sure to carry our maintenance as

Wipe water off carefully with a soft cloth. The chassis, in particular, should be taken the chassis, in particular, should be taken thoroughly dried. Oil anew all moving parts because their oil has probably been washed away by water. Adhesive fixing othe serios, etc., may have been weakened by water. It is recommended to refix them with new adhesive. Tamiys grays Oil gets under water and protects metal surfaces. Use it on moving parts.

Remove all the connectors and wipe off water from the whole mechanism. Then, remove it from the car and dry it in an airy place in the shade. If the receiver is wet inside, remove the cashig, wipe off water, but the care it is not all the care it is not to the care it is not an air water or sall twater, are fully index it with clean water. After it has dried completely comy out a performance of the care in the care is the care in the care in the care is the care in the



ance test. If it does not work, have it serviced by the manufacturer or his agent. As for the electric motor and speed control switch, it is recommended to apply Oil Spray or similar after carefully wiping off all water. Also dry the battery thoroughly. *The RC mechanism contains precision electric circuits. Do not attempt to take









MONSTER BEETLE Q.D.

New you can eithy car musting action with Tamiya's Outo Dave and contributed or series. The ever poorable in Outof Dave from Must diej on the body, snapon the east quast, installa batteries, and you've and either outoff of the outoff of the outoff or of early named, desired in the outoff of the revenue. The Normal or furth opport gear seekth, adds to its versality, feeding que for honorar a powerful feed of the contributed of the contributed of the contributed of the contributed the contributed of the contributed continued to the contributed the contributed of the contributed the contribut

block graffestinnin

Stelle 1940. Control large Titlere

Owen John Titlere

Owen Jo





MIDNIGHT PUMPKIN Q.D.

Terripid Quick Dries series can provide everyore with the fun and excitement of controlling as RV with the fun and excitement of controlling as RV can. The car is factory assembled and aimset reads to run. Steering is rigital proportional right and with and the speed control uses variable forward and reverse. Normal or Turbo speed gar wishth, adds to the excitement, Sealed gast box houses a powerful electric motor, and precision differential goaring. The car rides on huge chursly tree and the box depicts that all-time-functors 33 Ford Ford pickup truck.

Nobel provincescent & Color. 154. © Secural Trents. 20ther. Occurs with Notes. © Areas Areas. 20ther. © When I height 20ther. 20ther.





THUNDER SHOT Q.D.

Simple Guide New York 1990

Simple Guide New York 1990

Simple Guide New York 1990

Off load route. The care is factory assembled, and ready to run. It not require the installation of between York 1990

Letters Steering is digital proportional right and left, tested to be a special proportional right and left, tested to be a special proportional right and left, tested to be a special proportional right and left, the special proportional right and left, the special proportional right and left, the special proportional right and left, and the special right and left, and l

© Dennik steht Yffrem € Öursell height. 12 mm € Beheibeling i Steht Ste





SUPER SABRE Q.D. A-75-te-775- QD Tarriva's Quick Drive RC series provides evenone

with the fund and exclusionant of radio controlled rac ing, without any assembly. The Sper Sabre Quick many and the special controlled the controlled and controlled and controlled the special controlled and controlled and currently the statement of best first seeming, and a two step forward and fixed special seeming, and a two step forward and fixed special seeming and and the statement seeming seeming special controlled and statement. Seeming speed open seeming seeming seeming seeming.

Which reconcurrent @ Call 154 @ Charol length 175 @ Excell with 75 Time @ Charol length 175 me @ Excell length 55 (Stern) & Start Frence @ Charol length 175 me @ Excell stall via on Appara. Dispose @ Excellent for 20 20 me of 20 percent for 20 20 perce





THUNDER DRAGON Q.D.

Tamiya's Quick Drive RC series provides everyone with the fun and excitement of radio controlled racing, without any assembly. The Theories Depaid for the provided representation of the provided racing, without any assembly and the Theories Depaid for and performance seen on full-stood kit assemblied RC cars, yet it only requires the installation of batteries to be off and running. It features digital proportional steems, and a variable forward and reverse speed controller. Also, the Normal and Turbo speed gear switch adds to the excitement. Sealed gets to the part switch adds to the excitement. Sealed gets to the

Octobel specifications) ◆ Scale 154 ◆ Octobel longth, II2m ◆ Octobel specifications) ◆ Scale 154 ◆ Octobel longth, II2m ◆ Octobel specification of the Scale specification of the other prod Appear, Kingon ◆ Fire wedshipmanners Front 2027mm, in IZ73mm ◆ Body topical motion one ◆ Frame Engineering (Intelligence of Scale Sc





O DASH-3 SHOOTING STAR Q.D. サッシュ3号注意(シューティンブスター) Q.D.

Serviyal, Quick Drine RC peries can provide everyone with the flux and exchement or controlling as RC with the flux and exchement or controlling as RC prison. The Dashh-S Shooting Star Quick Drine has the sophististication and performance seen on full-sized the assembled RC cars and it comes aimont energy to run. It flexibutes original proportional elevering, and a sophistic proportional determination or Turbo speed gear seatch adds to the exchement. Sealed gear both houses a powerful electron tooks and precision differential gearing. Set in-cludes a whell can trigger type 2 channel fluxership.

ped Appa. Sign © to endedlatement frost 287:00 127 less © topos to ensure esse © trans Engineers conceivage hope © superioris. Frost endependent severy a relief green of superioris. Frost ender perioris of the ender green © construct (15th.) I while the lay speed to be forced to ender of the ender





DASH-1 EMPEROR Q.D. グッシュ1号 皇帝(エンベラー) QD



DASH-0 HORIZON Q.D. グッシュ 0号・地平 (ホライゾン) QD







WAVANTE 2001 Q.D.

he skin and elegant body styling of the PIC Awartle 501 is reproduced in '14' scale, joining the Clark time lineau, The Awartle 2001 GD is latory assemted, and ready to run. It only requires the installation of the control of the control of the proportional series, and a variable form of glat proportional controller. The Normal or Tutto speed gear switch dols to the excitement. Sealed gear box houses a coneful electric motor, and precision differential

Model quest'autiens

Soule 154 € Chemil Impth. Silvens
all width. Filters

Ground Chemil Impth. Silvens

Silvens





THE HORNET

(h— #->r)

Light weight and high power result in superb per
formance and the Home has achieved this. The use
of a lough bathois frameshasting the weight down to
a minimum. Ask and have high the weight down to
a minimum. Ask and have high the weight down to
a minimum. Ask and have high the high of
60 types motor provides the power to satisfy beginner and expert alike. With many of the features of the
popular Grasshopper, but with the upgrade of lifes

popular Grasshopper, but with the upgrade of lifes

In some of the wild and desolate areas of Southern California, buggy racing was born. These four which are normally of a single seal design constituted from welded steel tubing for lightness and powered by highly tuned racing engines. Speeds of up to 200 kmh are not unusual, over rough ternain.

Nodel Soprification © Scale 1719 © Overall length attempt overall solds. 20mm © Overall height 150mm © thheelbas 21mm © Iread Form © Overall People 150mm © thheelbas 21mm © Iread Form 150mm, new 150mm © Consul cleaned Scale overall solds of the Irea overall solds of the Irea of Irea of Irea over A Irea overall solds of Irea overall solds of Irea overall Irea of Irea overall Irea of Irea over Scale overall Irea overall Irea overall Irea overall Irea over Scale overall Irea over Irea overall Irea overall Irea over Scale overall Irea overall Irea overall Irea overall Irea overall Irea over Scale overall Irea over Scale Irea overall Irea ove





THE GRASSHOPPER II

SUPER SABRE







TERRA SCORCHER

AD-Fro- 4WD

Race proven 4WD mechanics are wrapped in fundistic body on this highly applicational but eas constructed off road roace. Motor power is training to be all one of the province of

contraction or make receive statements and contraction of the contract



73 VANQUISH

A robust high performance, four-wheel-drive off to race with fremendous potential has arrived on It RC racing scene. The motor is mounted arriskship for the best stability, and the power is efficient becomined to all four wheelers as a store of the situ trains, plus a third, ball type center differential maximum cornering maneuversability. Suspensis system is doubte wishbone all amount with color or of filled damper units at all corners. All of the R components are neatly packaged, into a stam.

Whitel Specifications) ⊕ Scale 150 ⊕ Ownell length 4 ⊕ Ownell width 20 km ⊕ Ownell length 140 km ⊕ White 27 km ⊕ Tead front & new 20 km ⊕ Minimum guintle of Arms ⊕ Tead front & new 20 km ⊕ Minimum guanti clin Arms ⊕ Tead & new 30 km ⊕ Minimum guanti clin diameter Front & new 30 km m ⊕ Scale Philycabonie ⊕ Absorrance in the 40 km m ⊕ Scale pain m whitel prints





FIRE DRAGON

Race proven 4WD mechanics are wrapped in a futuristic body on this highly sophisticated but easily constructed off road racer. Motor power is transmitted to all four wheels efficiently by using a steel propeller shaft for a minimum of friction loss. 4 wheel





The ultra sleek wedge shaped body styling is com-bined with state of the art shaft drive 4 wheel drive mechanics in this off road racer. Steel center drive shaft transmits the motor power to all 4 wheels affi-





SAINT DRAGON せイントドラコ: The elegant and sleek body silhouette of the Saint Dragon is matched to nimble ZWD off-road racing mechanics. The chassis is a light and sturdy bathfub type. Four wheel independent double withbone sur-





Model specificationi ⊕ Scale 1/10th. ⊕Covrail length. 47feren. ⊕ Derail width 270mm. ⊕Covrail height. 170mm. ⊕ Wheelbure "Frem. ⊕ Bread. From 275mm. mar 212mm. ⊕ Minimum ground discussors 27mm. ⊕ Height fully repageed Approximately 1370gms. The wideblamwiser Frost 2017tens, nor 40th from 6 Sody and mag Polycarbonate (Issail) \$\overline{\text{Street}}\$ in your wideblam (\$\overline{\text{Street}}\$) in or or empressing placis. \$\overline{\text{Supplements}}\$ in Supplement from which independent objects of or empressing placis. \$\overline{\text{Supplements}}\$ in Supplement so in spread, \$\overline{\text{Supplements}}\$ in \$\overline{\text{Supplements}}\$ in Supplement of supplement of \$\overline{\text{Supplements}}\$ in \$\overline{\text{Su



*Specifications are subject to change without notice.



ASTUTE 7272-1

Enthysis new max wheel of him of it coulder, the Astulan This RCC race has been developed for high level competition use, and its amazing performance will astify the most discriminating PC coding embussatisfy the most discriminating PC coding embussatisfy the most discriminating PC coding embustories suspension invitem has adjustable upper arms and cambre angle. Even the max wheel to-exingle can be altered through use of adjustable lookins. Mest be altered through use of adjustable lookins. Mest be altered through use of adjustable lookins. Mest have been also as the suppersion pixel points.

Chicles and decidence of courte 1998, decident impair, bit plates decidence of courte 1998, decidence and courte 1998. Judicine. Decidence 1998 of the coupping of the control of courte 1998, decidence or control of the control of the control of the courte 1998. Decidence of the courte 1998, decidence or courte 1998, decidence of the courte 1998, decidence 1998, decidenc





35 AVANTE 2001

The Please is back!...With a mission to shape the Mutter of four-wheel drive efficient origin. The motion is mounted withouth or one best stability, and the steel propeller shaft. Both front and man peur boxis steel propeller shaft. Both front and man peur boxis incorporate differentials, and a third, ball type center offerential is used for the best connecing performance. Suspension system is doubte-wishborne all around with coll one or of filled deeper units at all cournels. Art-level stabilizers are incorporated on both resp... The Auster God is a 4VO notice deem come year. The Auster God is a 4VO notice deem come seen. The Auster God is a 4VO notice deem come.

hold Sportfurstenni @ Lois 190h @ Oward laught 25mm Oward with 25mm @ Oward Ingire 180mm @ Netherbauform @ Next Freez 200mm and 200mm @ Netherbausen @ Next Freez 200mm and 200mm @ Netherbauform has a second of the second of the second of the Orderhamer Force 300mm and 200mm @ Back Physical Acus Force 300mm @ Despread with two cold ower of tilled dispress of the Motor @ Despread with two cold ower of tilled dispress on Next Second Second Second Oward Second Oward Second Next Second Second Second Second Second Next Second Secon





MANTA RAY

Will be simple contribution and sparse potential. Notice 18 kg in contribution and temporarises for PC chasses of impact the separation for PC chasses of impact the seatest free in his homeoporthy as the rest of the major possible of the possible of the

Media generalizatione of country to the control trains in the following distance of country of the country of t



79 EGRESS

of high performance raconversed components from the granufuse, front and mere pass boses incorposa a precision ball high differential, and in addition, content brough adjation is used for the best distribution of available power. The four wheel independent double withbook automation spatin has adjusted upper arms, and the cambor angle can be attered and the cambor and the property of the property of the property of the property of the uniform the property of the property assistant unified for maximum rigidity and weight saving. The Egypens was created to dominate RCC compet-

Model questications @ Scale 1000. @Owned length 420©Dental bash 20000. @Consul bash 10000. @Chemis

Dental bash 20000. @Consul bash 10000. @Chemis

Dental bash 20000. @Chemis bash 200000. @Chemis bash 20000. @Chemis bash 200







PORSCHE 959

The 50th Perio Dater Rally ware Prescribe 60th starting first and according facinity in the 4 wheel drive first and according facinity in the 4 wheel drive first first and according first 6 sylveder regime that pocularity for the prescribe facinity for the prescribe facinity for the first facinity for the first facinity for the first first facinity for the first facinity facinity for the first facinity facinity for the first facinity for the first facinity for the first facinity for the first facinity facinity facinity facinity facinity facinity facinity for the first facinity facinity for the first facinity f

Model Spredigations of Scient 331 to Owned Single Minimum Owned Index (Thomas Owned Index) Disson of Minimum Owned Index (Thomas Owned Index) Disson of Minimum Owned Index (Thomas Owned





TOYOTA CELICA Gr. B Miss.

In 19 - 12 1) 25 Gr. B

The Toyota firm, with their Celica Gr. B raily racer, dominated the tohuring Safari Raily, for three unbelievable consecutive years, in 1984, 65, and 81.

unbelievable consociative years, in 1984 68, and its proving that their automotive behaniously can sale the abune this race provides. Tamiya's radio control of Toyota Cellica raily racer was designed with a sale y concept, for on or off road running as with the full steed car. If incorporates a midatilip mounter motive and shaft driven, full-time, 4WD mechanics plays context differential. Frost and rear suspension is indispondent double wishboors byte with stabilities at frost. The billion middle ophycarbonate body it af frost. The billion middle ophycarbonate body is



. Specifications are subject to change without notice.



LOTUS HONDA 99T

Incorporating Honda's awesome V6 cylinder huttochapped engine, and an active computered suspension system, the Lobis Honda 98T Formula Chie racer was straked a top contender for the 1987 season. This RC mode provides you the same acclaiment as the full stand counterpart. The FIPP doclaiment as the full stand counterpart. The FIPP doclaiment as the full stand counterpart. The FIPP doseason to the full standard counterpart of the full standard counterpart. The FIPP dote regimenting plastic front end, incorporates the suspension area and front level, Julie of tracts proversi 3 point suspension system assure superb stabilty on the competition scene.





WILLIAMS FW-11B HONDA ウオリアムズドW-11B カンダ

The Williams racing team who won the 1996 constructor's this continued their streak of withoutes or through the 1997 Grand Pits season with the refine of PWIII Promise One store. The PC model promise The PRO model promise the suppression areas and frost very. Use of tract proven 3 point suspension system assure superticibility for competition performance.

Model specification ⊕ Scale 100 ⊕ Dennel Englis, 20m ⊕ Whee © Overall width 100m ⊕ Dennel Englis 20m ⊕ Whee 20mm ⊕ Englis 100m ⊕ Dennel 100mm ⊕ Whee 20mm ⊕ Englis 100mm ⊕ 100mm ⊕ Weight Life prof. Agrees With ⊕ The weight Limiter to 100mm ⊕ 100m



20



LOTUS 102B JUDD

To commemorate Tarriya's spo

season, vaniva resistant the Lottus Yords Judd racer as a 11th scale electric powered raidio control model. The chassishame uses injohelpit and stury FIFF seam-double dock construction. The hort and a collesered double dock construction. The hort and a collesered double dock construction. The hort and as control grand, while he here use as a single, cost overtryin supportation. I system. A the performed Society by supportation system. A beginning of the control grand of the season of the control of the control grand of the control of th

all width 200 mm 6 Owned Inspire Nome @ Wheeld of Tread Front 150 mm, and 150 mm 6 Whiteple failing on pain. 150 kg & Free widthsharmers: Force 200 km mm, in pain. 150 kg & Free widthsharmers: Force 200 km mm, or not use in Freet widthsynchronton & France FEE' challed deck to pain freet widthsynchronton & Grammer Harmer & 200 km mm, or not of charger or mit of first flower distingential grammers and the first transport to the first flower courses: Europa & Egyptom or or Europa New 200 Kg Systems or or the first flower Europa & Egyptom or or the first flower flower Europa & Egyptom or or the first flower flower Europa & Egyptom or or the first flower flower flower Europa & Egyptom or or the first flower flower



HONDA NSX



The second secon





フーバーアスチュート
Upgraded to meet the newest in compet ments, the Super Assute offers the dyna

whose-time of road performance, the chasses selected in the chasses of t

• Peters anne, solitoria del Content Suglia, Peters del Content Suglia, et la Conten





BEAR HAWK ペプホーク Considering that the first RIC buggy may determine

when the property of the second section of the section of the second section of the section sectin section section section section section section section section





JAGUAR XJR-12



TOYOTA CELICA S... RALLY [32]

1/10th SCALE (58096) 7.2Vv->>5-1->>5/498



MANTA RAY Q.D.

Mark Ry, Its existance of persection by the place have the common to the common to the common to the successful of the common to the common to common to the common to the common to the successful of the common to Marks Righ Cubic Drive has the suphistication and performance seen on full segled at suspending RC cars. It flexitues digital propriored altering, and a performance seen on full segled at suspending RC cars. It flexitues digital propriored attempts, and performance seen on full segled as performance seen on subsequent performance seen on subsequent performance seen on subsequent performance seen on subsequent performance seen on the subsequent performance seen on the subsequent performance seen to the subsequent performance seen on the subsequent performance seen on the performance seen on the subsequent performance seen on the performance seen on the performance performanc

Into the exciting RC off-road racing world.

Asked quoticational \$\insert{\text{Size}}\$ is \$14. \$\insert{\text{Q-road}}\$ is such to

Asked quoticational \$\insert{\text{Size}}\$ is \$14. \$\insert{\text{Q-road}}\$ is such to

Asked \$\insert{\text{Q-road}}\$ is \$14. \$\in





CLOD BUSTER Q.D.

A \$190.9 \tag{1.00} A \$10.00 \tag{1.00} A \$10.

at width, Admin of Chinal Inspir. 2 Johns & Wilhesburner 19 *Brail For and on 20 them of Proper Institution appeal in a *Brail For and on 20 them of Proper Institution appeal in a part resident reside frame. Engineering plants monocopies \$\times\$ \text{Summary through the proper in the Society of the
\$\times\$ concerning property devices mode appeals with
\$\times\$ in concerning property devices mode appeals and
\$\times\$ in the property of the property of the
\$\times\$ in the \$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$ in the
\$\times\$



. Specifications are subject to change without notice



For the 1989 Formula One racing season, the Fendam entered a revolutionary F189 race car. The w

stam element a relocationary in the face of all new plantage data from the feeting. Under this accordance body she if a commany approach, 25 feet displacement as a commanly approach, 25 feet displacement as a commanly approach, 25 feet displacement as feeting and approach as a comman and approach as a comman and approach as a comman feeting and approach as a command and approach as a series of series of

DANAM Sportrainment & Scale USS © Describ Impe Onnail with 200 mm © Onnail Impelle 1880 mm © 200 mm Encod Invot Int Sport, may latered Whiteght I pal Apper, 1070; © for well-trainmenter Force 300 feet Impelle & Dody Follysatherapie © Frent Effe double

to final danger control of the figure conserved ground gro





TYRRELL 019 FORD

round at San Marrol in the model of May, it uses very distinctive, anerhedra staped from very for proved aerodynamic performance. Service in model can provide you the same excitement as fulf-steed counterpart. The chassistrame uses a FI somi doubte dock unit with the preferred Sports is perision system. The front end is coll spring damp while the rare uses a single coll over of filled dam or unit. A precision ball type differential is used the best along performance.

When I was a support of the support





PORSCHE 956 RM. Mk.5 ポルシェ956 レーシングマスター Mk. 5

This high performance Porsche 956 R/C model was suspension vehicle with a front independent suspension using coil springs for dampning, and the near suspension is a single point adjustable serving unit, newly designed for competition, Adjustable sabilities revely designed for competition, Adjustable sabilities is ighteelight FIPF of the double dock injus. Filst coil speed confect is adjustable for soft and hard pair-ing, and uses a possible confact view, it is the fastest FIPC or Territy has yet designed.

About the prototype. • The Porsche 956 is a group C racing vehicle developed for the World Endurance Championships. Its aerodynamic body with a refin-ed ground effect undersurface uses a 2648cc oppos-Model Specifications

• Scale 152. • Overall length 177-mos
Overall length 177-mos
Overall length 178-mos

Overall length 178-mos
Overall length 178-mos

Overall length 178-mos

Overall length 178-mos

Overall length 178-mos

Overall length 178-mos

Overall length 178-mos

Overall length 178-mos

Overall length 178-mos

Overall length 178-mos

Overall length 178-mos

Overall length 178-mos

Overall length 178-mos

Overall length 178-mos

Overall length 178-mos

Overall length 178-mos

Overall length 178-mos

Overall length 178-mos

Overall lengt



TOYOTA TOM'S 84C RM. Mk. 6 トロクトムス BIC レーシングマスター Mix. 6

About the prototype . Toyota TOM'S 84C took a 7th place at the World Endurance Championships held at the Fuji Speedway, Japan in 1984. The first five phaces were taken up by the well known Porsche 956. It utilizes a modified Toyota 47-67 turbo engine which produces over 500hp, and it is expected to be a for-

Nobel (professions) & Sode 137 & Overal Iraph, 150m & Overal Iraph, 150m











VIEW PK 8002X IMMS GTO

NISsan's S002X GDT care first entered the American
IMSA disternational Motor Sports Association com-petition in 1981, and has displayed by parked perior
intered ever since. Nissan's competitive racing
components are wasped in a production car local
line body shell. Eurhysa RC model provides you the
fixelige performance and aggressive looks of the fullliced counterpart. The impact sessitant resin modi-of by December 1991.





his conditional RC which use a time speed parton that is shifted via the transmitter for power-ful four whee drive in first goar, a how wheel drive at medium speed in any give and 22 wheel high speed running in 340 gear. The geather comes factory assembled and the remaining components of the verticle assemble much like the full stadd Toylota. Huge sizes and the powerful shigh torque RE-70034 molto provide specialized performance for the good.

CKFOOT



FORD F-150 RANGER BLACKFOOT







MONSTER BEETLE

This is a custom, high rise, külkisvaagen Beeter acid control off load buggy. The sill and humonous features of this car stand out on or off the task. The high operformance competitions 569 lype motor is in charge to the competition 569 lype motor is the mode about the competition 569 lype motor is the mode about the competition of the race provide the mode about the competition of the race provide the competition of the

prising unficile with the edge on performance.

Which is constanted. ■ kale 100 ■ Owned length of them.

A change with 2 owned owned by the constant of the constant of the constant owned owned by the constant of the constant owned ow





MONSTER VAN LUNCH BOX

It is bested up custom staff, high rise Dodge at a favey gain plo, done the numer's tasks, and and the sport is all about it is an easy to share the controlled controlled controlled controlled controlled controlled controlled to the controlled controlled controlled to the controlled co





プリ MUD BLASTER

truck now folios higher than exer, and is known as the "Mud Blaster". A high performance competition electric motor is included along with the four heavy only coil spring shock absorbers. Chassis is the race proven AIST resis space frame, light in weight and externey story. High performance differential gain-standard on this highly versable radio controlled as standard on this highly versable radio controlled as the model of the standard on this highly versable radio controlled as the model of the standard on the highly versable radio controlled as

Debel Specification & Scale 137 © Oracle length Allem (Local) and Delten @ Oracle planty (Done of Arbertine Plant) & Schlem & Oracle planty (Done of Arbertine Plant) & Schlem & Debel Specification of the Arbertine Planty (Done of Arbertine) and Debel Specification of the Arbertine Planty (Done of Arbertine) (DODero) & Schlem (Done of Arbertine) & Schlem (



Turning an elegand classic line a beast. Nex, with custom tracking the dream is easily activened. The Act contains that altimetaworks of Yord F000 joint by took fitted out with glaint oversized times four stopping performance after facts. Chassis is a light and stroty ARIS retain low type. Sealed glaint box in an independent leveling axis type while the nex uses a rolling, rigid axis by se supermision. Detailed impact resistant injection modisor book.

Nodel specificationi ⊕ scale 152 ⊕ Oseal length. Mile ⊕ Oseal width, 20thern ⊕ Oseal beight. 20thern ⊕ in Needla 20thern ⊕ Seal from 12 Them, are a Colorine ⊕ Milestonian grass classrates. 20thern ⊕ Milestonian organization classrates. 20thern ⊕ Seal of the Seal of the Colorina Seal of the Seal





48



TOYOTA HILLIX MONSTER RACER





NISSAN® KING CAR®

The Tamiya mode of Nasaath popular King Cata pro-trict may a mode of Nasaath popular King Cata pro-trict was part it term diameter, semi-posumatic consistencing parts to house a prosition that tipe of interestal that protects gazes and sharfs from a consistency of the consistency of the consistency of condet withforce suggestion system is damped by sign passing, only one of filled damper units and protection of the consistency of the consistenc





CLOD BUSTER

The ultimate in an all-ternain craptor, using mancromities their and a cotton paint job will attack continue their and a cotton paint job will attack admires both young and old. They just card reseat the action and exclament these cultomorate placup trucks ofter. The Clod Buster ricks on mammoth Yomen seen powersach robot like tree, camped by eight long stocke coll shocks, and is powered by two 5-60 pps motion. It uses four-where-drives and fourceited pound clearance taking this 400mm whiche over most any obstacle in its path.

Over Most any obsisce in its pater.

Oncell with Storm & Oncell length six Oncell length Storm & Teach Control and Storm & Storm & Teach & Teach Control and Storm & Teach & Teach Control and Storm & Teach & Tea





BULL HEAD

Relief high on Worm diameter earth-kicking tires. Belling high on Worm diameter earth-kicking tires. Belling high on Worm diameter selection occorrolled monater vehicles. Tarriya engineers have faithfully reproduced the massive semi-rig body styling that is seen moving majestically down the Builhead is dismorped by eight from printer coll shocks, and is powered by less powerful electric motors. It uses a flegtly operitheticated foru-weel-ordine and top-indicated foru-weel-ordine and the assessment power. mechanics, and so-electing ground clearance, the glant can takk most any ground clearance, the glant can takk most ground clearance in the glant ground ground

Model Spotfactions) is taken 1900 in Overall length. Size on Overall length Size of Overall





PORSCHE 9620

I of The STATE of






and 9247 LC2 in LC2 is Lancia? Intel Group C racer, which made is obtat during the 1900 season. Its superb high nord ability has enabled it to state the pole pos-ing of the 1900 season. Its superb high nord properties of the 1900 season in the 1900 season to consider the of transition season. In LC2 was supplied with the 1900 season to consider the 1900 season to consider the design to consider the 1900 season to consider the classification RC2 minister mode both in CM5000s. All the necessary items, including RC2 is and NG2 between the 1900 season to con-trol and 1900 season the 1900 season the





FERRARI TESTAROSSA

he Testanoses was unrelied in October 1984 as a uccessor to Fernar's top model 88512. Its smooth working Prinntains designed body housed a 12 lyrinder, 4940c, COHC 4 valve engine which pro-uces 590th; It is reputed to be one of the faster induction cars in the world at 290km/h. This ameter 124 scale. RPC car provide the action and attention 124 scale. The control of the faster that is not controlling a precision RC minister model oft in or custoos. All the necessary terms, in the controlling a precision of the controlling the controlling a precision RC minister model of the custom of the controlling as the controlling the con



PORSCHE 961

The Persche designated 981 is an endurance racer secondors of the sensitional and stochnology conceeding 981. The sensitional and stochnology conceeding 981. The sensitional and stochnology conceeding 981. The sensitional sensition for the sensitional sensition of the sensition for the sensition of the sensition of the sensition section and finds of controlling a precision RC section and finds of controlling a precision RC section and finds of controlling a precision RC section sensition sensition



. Specifications are subject to change without notice.



プ COUNTACH 5000 QUATTROVALVOLE

The Countach has been Lumborghini's topolitims show as since its debut as a production model in 973. The Countach 5000 Quantificantholies was shown at the 1860 Genew Mobile Dixin, incorporating 4 and the 1860 Genew Mobile Dixin, incorporating 4 for the suppression, seedige shaped shifting captures seed of the countage of the suppression scale root car enthulations all over the world. The Sample of the 1861 Countage is suppression scale root of a high performance ratio contributed can be suppressed to the suppression scale root of the superior superior suppression scale root of the superior superior suppression scale root of the superior superi

(Charger varies according to country.



Tamtech 20



The Timest overall combat tank during Wind War 2. Model will accept up to four Charmels of radio con tell for harret rotation and gun flashing light. A minimum of the otherwise is required for coperation, child/sully finished with metal rock, the catapille micks are made from a new type of plastic for long and select of manimum and catapille micks are made from a new type of plastic for long and select of manimum and catapille micks are made to the manimum. A minimum and catapille micks are made to the prototype e Entering the front lines state and the prototype e Entering the front lines state middle the general King Tigor tank was recarded.

In 1944, the German King Tiger tank was regards at the most formidable battle last to be introduced at the most formidable battle last to be introduced sing the conflict. Mounting the well known Bierr model 48 gun, plus two 7 /6/mm machine guns, and covered by a Maybach, water cooled, VIV2 engin this tank had a too speed of Hellemith. A bital 42° King Tigers were produced during the war. Mount specification: 4 Sole 131. 4° Overall length 450m. Overall width 256m. 4° Overall length Fritten 4° Usins





2 WEST GERMAN LEOPARD A4 西ドイツ・レオンジレドA4戦車

This is a moviel of the West German latest tank. You

About the prototype • The newest improved type of West German Leopard tank is the A4 which is one of the most formidable combat vehicles of the world.

| Model Specifications|

Scale 1/16

Overall length 600mm

Overall width: 256mm

Overall height: 567mm

Minimum ground clearance; 25mm

Weight fully equipped: about 46g

Bods: Symme resin

Frame: dutalumm

Moter power in tamenta.

Body. Symme mosi. In frame of duratures in Motor power is transmis-ted through clusters. The tasks can be made to run in either for-ward or sweme direction and simultaneously steer left or right in Literal motor tasks. In All most advantage of the supermission supermission steel symmetry and production of the supermission supermission steel symmetry for protesting-cal operation in Motors 540 type in Crear scales 103.7 in Pereir source 7.2 Marcing Pack in Radia control system to be used 2 channel proportional (not included). It lank can climb a 40 degree excline.





WEST GERMAN GEPARD ** 西ドイツ・ゲベルト対学設定

This is a radio controlled model which can be enjoyed

About the prototype . The West German Gepard is

Wodel Specifications)

Scale 1/16

Overall length: #Himm

Overall height: 216mm

Minimum pound clearance 28mm

Timple fully equipped about Sig

Nody Symme nexts

Frame duratums

Only Symme nexts

Frame duratums

Only sexts. Soly Myretie resid & Frame dissalarini & Drine until system. Sein clutch mechanish, forwardreven, pivot and gradual farming & Turret molution; XXVI gars movement up and down, near radiar rotation & Lindel metal tasks & Radio control system used channed proportional system is minimum requirement (not included) & Tower source Taminy 3.73 Racing Pack.





TAMTECH R/C SYSTEM

The 1/24 scale Tamtech radio control series can models are designed for radio control operation, to provide the modeler with the thrill and satisfaction of building and controlling a precision scale miniature model. Enjoy organizing races and experience the true meaning of this





PORSCHE 9620 The Tamtech Car contains the same binh ner

formance car as in the Tamtech Complete Kit except for the Tamtech radio control unit, and Ni-Cd 7.2V-270mAh Tampack battery. This kit allows you to collect the entire series of cars without radio control units, adding the radio



PORSCHE 961

The Porsche 961 is an endurance racer descendent of the 959. The Car Only Kit contains the same highly detailed high performance car as in the Tamtech Complete Kit except for RIC unit, battery and charger, Chassis provides a choice of a 104mm or 97mm wheelbase

TRANSMITTER AND

RECEIVER TAMTECH 201 B/C LINIT The Tamtech radio control unit was developed in conjunction with the Futaba Corporation exclusively for the Tamtech radio control can series. The amplifier operated speed controller



and receiver are combined in the C.P.R. (Control Processing Receiver) unit and obtains its power from the running battery. The Tamtech radio control unit can be widely used in miniature cars. Different frequencies are

presently available for the radio unit. BATTERY & CHARGER



TAMIYA Ni-Cd 7.2V-270mAh

TAMPACK BATTERY This is a powerful, small Ni-Cd batters developed for the Tamtech RIC car series. It consists of six 1.2V-270mAh Ni-Cd batteries in series, to provide excellent acceleration and performance it is also economical, as it can be charged more than 500 times.



TAMIYA Ni-Cd 7.2V-270mAh TAMPACK RATTERY OHICK

This charger enables you to quick charge you 7.2V Tampack hattery in about 15 minutes us. ing a car cigarette lighter. The charger is equipned with a timer and a pilot lamp to ensure safe trouble free charging of your battery.

SPARE PARTS Tamiva provides a wide range of spare parts

for you to keep your Tamtech RIC car in top competition condition. Spare parts are necessary for maintenance and tuning up for races. Like large scale RIC models, adjustments are required to keep the lead at the track. Spare parts, such as decals, wheels, motor, body parts sets, differential gears, etc. are available.



FK:180SH MINI-BLACK MOTOR This is a powerful performance electric motor

for the Tamtech radio controlled cars. The conly without any soldering. A good performing motor is a must in maintaining the high per formance of these radio controlled cars. Replace a worn out motor at an early period.



SPONGE TIRE A with WHEEL When out time hinder the performance of the car. Replace worn tires at an early stage to maintain stability and handling at the track. Tires are pre-fitted to the wheels for quick

replacement.

SPARE DECAL These decal sets are for redecorating, or replac ing dirty and damaged decals for the Tamtech



* 60	LANCIA LC2	470
C unit 🗂	EMW GTP	470
00 3	MUSTANG GTP	470
	FERRARE TESTAROSSA	470
The second	PORSONE 961	470
ry & .m	COUNTROH 5000	470
Charge		

CAR ONLY KIT	PORSCHE 962C
(A)	LANCIA LC2
	BMW GTP
	MUSTANG GTP

COMPLETE Car only hit PORSCHE 9620

nit & bettery	PORSCHE 961	4800
cluded.	COUNTRACH 9000	48007
E BODY SET	PORSCHE 9620	4000
250	LANGIA LC2	4000
-		

	TESTAROSSA	4001
	PORSONE 961	4001
	COUNTACH 5000	400
TECH 201 R/C	UNIT	
-	, Transmitter	

COR USE Streeting servo		4500		
CRYST	AL SET	RX/	TX	4500

For receiver & transmitter	
Ni-Cd 7:2V-270mAh TAMPACK BATTERY	

Ni-Cd 7:2V-270mAh TAMPACK QUICK CHARGER

LACK MOTOR	40
PONGE TIRE A with WHEEL	40

(4 pcs.)		-00
FRONT SP (4 pcs.)	ONGE TIRE	400
RE DECAL		
che 962C		- 400
ia LC2		- 400

FERENTIAL & PINION	T	****
rsche 961		40019
istano GTP		40016
W GTP-		40015
onsor Geest Lancia		40011
Goodsich 962		40010
ncia LC2		40000

GEAR SET	4000
TECH BALL BEARING SET	400
UNIT P-05N	

GUIDE TAMTECH



The 1/24 scale Tamtech RIC series car models are designed for radio control operation, to provide the modeler with the thrill and satisfaction of building and controlling a precision scale miniature model. These 1/24 scale radio models and have an overall length of about 20cm and width of 8cm. The compact size reguires only a minimum of space for running in or outdoors.



CPR (Control Processing Received unit Precision differential gearing

performance like new. The Car Only kit. RIC unit, replacement tires, motor, body parts. decals, etc. are available for routine mainte-

The Tamtech 201 two channel digital propor

Steering adjuster

amazing agility provides lots of wesatility and amusement for everyone. The RIC unit frequency crystals are easily interchangeable and different frequencies are presently available enabling you to race in groups.

The Tamtech 124 radio control cars are only

half the size of 1/12 scale models and have an

overall length of about 20cm, and a width of

about 8cm. This compact size requires a mini-

larger radio controlled cars. Crisp handling is

matched to a turning diameter of only 30cm.

plus smooth acceleration built within the car

Timed, speed, and ovrrikhana racing are some

The easiest way to make a race circuit is by outlining the course using vinyl tape, if the track is on carpet or a wooden floor. Outline by using chalk if its on asphalt or concrete. If you want more sophistication in your racing 2 x 2cm in size to fence off the circuit. Make sure to securely tape down the fence to avoid car bumpers getting stuck underneath the fence. Also remember to use tape that is weak in adhesive or you'll have a clean up mess at the end of your racino day. Don't forget to wipe off the chalk lines from the pavement too. Always construct the race track on a flat, hard **OUTLINING A RACE CIRCU**



The Tamtech radio control car series has all of the necessary equipment, including radio control unit and Ni-Cd battery which were designed just for this series. When you're new to the hobby it's nice to know that you have components that work together and not just what the hobby shop dealer might want you to buy. The Complete Kit contains the RIC unit. Ni-Cd battery and charger and the genuine

amtech quality spare parts will keep the car's

provide the highest standard of performance for these radio controlled cars. The amplifier boosted electronic speed controller and receiver are combined as part of the C.P.R. (Control Processing Received unit, which obning battery. The normal two channel two see. yo configuration is not seen in this radio control system, since the amplifier operated speed controller and receiver are combined as one unit. Only the steering servo can be recconnectors are prewired, eliminating tedious wiring chores. Even the steering servo is prewired to the unit. TAMTECH 201 RIC UNIT COMPONENTS

of the ways you can enjoy the Tamtech radio

The Tamtech radio controlled cars can be run

on thin carpet, wooden floors, asphalt or con-

crete pavement. The racing sponge tires used on the Tamtech RIC cars are designed to provide excellent grip and traction on these types of running surfaces.

Living room space is all you need to have competition races. If you want to organize indoor race competition, a 90 150cm width, 8 15m lap length race circuit will be more than enough space for competition excitement. You don't even have to worry about bad weather vehicles for the larger radio controlled cars them to train and keep your driving skills in top condition. With the Tamtech, you can have radio control excitement 24 hours a day

Here are some tips in constructing a more sophisticated race circuit. Use sheets of plywood firm thick and lay them out as shown. Cover the track using thin lavers of carpet for better oripping of the sponge tires.





Worries about cuerbeating the speed control heat sinks are done away with. The amplifier operated speed controller allows continuous running, fast or slow, without overheating problems. The speed control is a forward/reverse variable type, providing all of the excitement

Good nunning performance is difficult to obtain on slippery surfaces such as hard or viryl tiled floors. Also avoid running the car on surfaces that will impose too much of a load on the running components, such as thick carpet. bed covers, and soft sandy areas.

Construct fence using a flexible polyviryl rail ing and secure it with double sided tape wood screws and L shaped brackets, as shown. Though this will be a more costly project, you will have the satisfaction of owning a race circuit of your own.

TIPS FOR CIRCUIT LAYOUT A circuit that's too long, short, narrow or wide

will spoil the excitement of racing the Tamtech BIC cars. The track width should be at least 80 - 150cm, and should have a straight numbing stretch for at least 8 20m to allow the car to run at maximum speed. The basic layout can be as seen at larger radio control car circuits. but be careful not to make the layout too comnley or too plain. The race circuit should include high speed corners, "S" turns, and hair pin curves, to test driving skills. Design the racing circuit with the driver's vision in mind. If you are planning on organizing races allow plenty of room for at least six speeding racers.

PRODUCE AN ACTION DIORAMA

Additional timing towers, pit stalls, sponsor advertisements, and other 1/24 scale car models set around the area can convert the Tamtech race circuit into a beautiful and functional racing diorama. The Tamtech 1/24 scale chassis can be fitted with many of the 1/24 scale model bodies already available from Tamiya, such as the Mercedes-Benz 500SEC, and the BMW M635CSi. These bodies can be fitted with only minor modifications Others can also be fitted if the wheel base and tread match up. A life like, action packed. diorama using the Tamtech RIC cars is really

not that difficult to do. WHEN USING SLOT CAR

CIRCUITS



Tamtech

TAMIYATAMTECH OUTDOOR RIC CIRCUIT ● Tack width: 1.5 1.8m ● Lap length: 53m

TAMINATAMTECH INDOOR RIC CIRCUIT CIRCUIT LAYOUT DESIGN TYPE A ● Track width: 0.65 0.85m ● Lao length: 23m othoro above • 36 x 35m CIRCUIT LAYOUT DESIGN TYPE B

cars will perform smoothly over the slots, reliving the slot car racing boom. Just remember to completely disconnect the electronics from the slot car unit, as they are no longer required. If the plug is left connected, it could cause radio interference.

CAUTIONS FOR RUNNING INDOORS

Running the car in rooms that have metal reinforced walls, could also result in radio inter ference problems. Old blinking fluorescent lamps, computers, television, and electrical appliances like air conditioners using large motors may also interfere with some frequencies. Avoid running the cars in these environ

 CONVERTING 1/24 SCALE MODELS INTO RIC CARS The 1/24 scale model cars are popular all over the world because of their size and details. The

Tamtech 1/24 scale car chassis can be used to convert many of these models into RIC vehicles. The wheel base and tread should be close to the chassis dimensions. Tamiyals Mercedes-Benz 500SEC, and the RMW M635CSi fit with only minor modifications.

BODIES THAT ARE SUITABLE FOR MODIFICATION are the same, only a minor modification is

necessary to fit the body. Refer to the dimensions shown. GET THE WHEELBASE RIGHT

The Tamtech chassis can accept up to 5mm differences in the wheelbase. Cut or sand off the intervening wheel arch on the fender to


 WHEN TREAD IS TOO WIDE When the tread is too wide and the tires are extending out too much from the fender, add blistered fenders using plastic sheet to smooth out the contours of the body TAMTECH CHASSIS DIMENSIONS

· WATCH THE HEIGHT OF THE C.P.R. UNIT

Check out body by fitting it to the Tamtech R/C car chassis with the C.P.R. unit mounted prior to deciding on the modification. Some cars with aerodynamic body styling have a low hood and rapidly sloped windshield which will get in the way of the C.P.R. unit. If the problem is slight, the chassis can be attached slightly rearward for a better fit

MOUNTING THE C.P.R. **UNIT SIDEWAYS** Certain bodies can be easily fitted when the

MAKING FLARED FENDERS





REQUIRED PLASTIC PARTS (1/2 size

WHEN USING THE TAMIYA 1/24 SCALE

TOYOTA HIACE QUICK DELIVERY BODY



BODY The compact size of Tamtech cars enable you to do your own body designing with ease. You can do major remodeling on a kit body or build one from scratch. With Tamtech radio control cars, your sought after dream car can be a reality. Spend time at the drawing board, select of-a-kind vehicle.

CPR unit is mounted sideways. When doing

this smooth out the bumps on the chassis and

secure the unit using double sided tape.



Tamtech radio controlled cars have two vital tuning points that enhance the overall performance of the car on differing road conditions.

 FRONT SUSPENSION The Tamtech radio controlled car's front suspension is a sophisticated independent coil damped type. The silver coil springs included in the kit are the normal type while the black are the soft type. Using the soft type provides

guicker steering (oversteering characteristics). 2 PINION GEAR

The Tamtech radio controlled car was design find within the kit, four different pinion nears. for altering car performance to track conditions. 8T, 10T, 12T, and 14T pinion opens are included. The more teeth, the higher the maximum speed, but weaker acceleration and shorter running time. A smaller pinion gear will pro-

vide the opposite performance with a lower top speed, but faster acceleration and a longer running time. When running indoors or in a racing circuit with many corners, use of the smaller pinion gears is recommended.



TROUBLE SHOOTING WHEN CAR DOES NOT STOP OR RUNS AWAY

WHEN CONNECTING BATTERY (i) Is the speed control trim on the transmitter properly adjusted? Adjust trim lever to stop

position of the car.

(2) Set neutral lever to the normal position 3 When adjustments can not be accomplish ed at the transmitter, adjust motor neutral adjuster trim on the C.P.R. unit.

CAR DOES NOT RUN STRAIGHT

(i) is the steering control trim on the transmit straight with stick at neutral.

AD HISTING STEEDING *Adjust by running car on flat surface.

. Keen steering control stick in neutral *When car runs to the right, slide trim lever to left for adjustment

. When car runs to the left slide trim lever to right for adjustment. 2) When adjustment can not be accom-

plished at the transmitter, readjust servo hom

and tie-rod length.



(2) Never hinder rotation of wheels while

 Aunid nulling loads or steep uphill climbing Remove all dirt and debris from shaft and cears.

Never run car when differential and gears are not meshing properly.

WHAT TO DO WHEN

HEAT PROTECTOR **ACTIVATES**

When your car suddenly stops running, there tivated. Immediately shut off receiver and check for cause. Correct problem and wait 15 minutes before turning on the receiver again ORSERVE THE FOLLOW-

ING CALITIONS Digital proportional units use the latest in electronic technology. Follow the instructions outlined below to avoid damage.

(1) Avoid short circuits Worn insulation on the wiring can result in a

short circuit, destroying battery and C.P.R. unit. Properly insulate worn cables using viny tape.



Connecting plugs The connectors can only be joined together in one way DO NOT USE FORCE! If they don't fit perfectly together, do not attempt to use force or it can ruin the C.P.R. unit

(3) Avoid running in standing water and rain. The C.P.R. unit and servo uses the latest in electronic technology. Avoid using the unit in wet or damo areas. Also be careful not to drop it. Take the utmost care when handling the unit. If the C.P.R. unit should accidentally get wet. immediately disconnect battery, clean and dry thoroughly, using a heat dryer. Consult with the

manufacturer if loss of control should occur. MAINTENANCE AFTER RIINNING . Use a brush and clean dry racs to committee

ly remove sand dirt, etc., and apply grease to cears and suspension. . Avoid using water, detergent, or spray oils for cleaning the car *Consult with the manufacturer for repairs.



1) Are the batteries fresh or recharged?

② Are all connectors properly plugged in?

② Do the wheels rotate smoothly? Are the

gears meshed properly? A differential and pi-

nion gear meshed improperly hinders rear

wheel rotation, activating the heat protector in-

stalled in the speed control amplifier. This cuts

■ LINSTARI E CONTROL OF THE CAR ① Are the batteries in the transmitter fresh? Check for possible radio interference from

off current flow temporarily.

· WHEN THE HEAT PROTECTOR ACTIVATES

gravel and soft sand areas.

The heat protector installed in the C.P.R. unit protects the speed control amplifier from over load by temporarily cutting off the current flow. destroy the speed control amplifier. Follow the instructions outlined below. Avoid running on thick carpet, bed covers.

C x 2.05mm Aluminum sheet

REQUIRED PARTS



CHARACTERIZING A CAR

There are a variety of car characters; fast with good cornering capability, and so forth. Cars assembled from kits come out up through the assembler's own techteristics.

1 MAYIMIIM SPEED AND **ACCELERATION** CAPABILITIES (GEAR RATIO AND SPEED)

At a given output power of the motor, the maximum speed and acceleration capabilities are determined by the gear ratio. With electric cars, the relation of the pinion gear on the motor shaft to the gear of the rear gear ratio with a smaller pinion gear (smaller number of teeth) and a larger gear on the rear axle. The opposite makes a low gear ratio. With a high gear ratio, the car has a better acceleration capability, but a limited maximum speed. A car with a low gear ratio has poor acceleration but a higher

maximum speed A car with high gear ratio is suitable for a technical course which is built with hair oin curves demanding low speed driving, while a car with a low gear ratio is for a speed course consisting of longer straightaways





The diameter of the drive tires are also related to the speed and acceleration characteristics. The larger the diameter of the drive tires are, the higher the speed of the car will develop within certain limitations.

2. UNDER STEERING AND **OVER STEERING**

(STEERING TENDENCY) When the steering wheel is turned, the car ever, most cars have the tendency to turn excessively or inadequately. These characteristics are called steering traits. Cars that turn excessively have over steering traits



and the others have under steering traits Cars that turn in close proportion to the control have neutral steering. This is hardly

STEFRING WHICH IS FASY TO CONTROL

A car with slight under steering is easy to when taking corners at a high speed. Even on a straight course, it is unstable. An under steering car has difficulty making sharp turns, and at a high speed it may not be able to take corners and could leave the course. In either case, excessive steering makes a car difficult to control.

FACTORS TO DETERMINE STEERING CHARACTERISTICS

The steering characteristics are affected by the difference between the traction of the front and rear tires. When the traction of the front tires is greater than that of the rear tires, the result is over steering. The opposite condition causes under steering Therefore, adjust the traction of the rear tires so that it is a little greater. You will then attain a slight degree of under steer-

The traction of a tire is determined by the weight it carries, by the area of contact of the tires on the road surface, and by the weight a tire carries, the larger the contact area becomes, and the softer a tire is the

ADJUSTMENT OF STEERING

*DECREASING OVER STEERING (1) Place a heavy load, such as batteries, at rear portion of the car.

(2) Replace the rear tires with larger ones or replace the front time with smaller ones. (3) Replace only the rear tires with sponge

*DECREASING UNDER STEERING (1) Place a heavy load at the front of the car (2) Install front tires that are larger

These three remedies are the basic ways to change steering characteristics. The traction of cars with suspension systems can spring tension, 30% -40% of the car's full weight should be on the front wheels and 70% -60% on the rear wheels.

WING

The wing attached on many racing cars is ning. With your radio controlled cars, the rear for improving the traction on the road. In this way, the gripping power of the rear wheel and the steering trait changes toward under-



fective the wing becomes, that is, the greater the down thrust on the rear wheels. Depend ing upon the way you adjust the wing, the superb stability on the high speed straights Such a car, also, will show a good adhesion down-force. However, it increases the air drag ment an ideal maneuverability will be

In order to run a radio controlled model smoothly and swiftly over differing road con ditions, the suspension system that joins the for buppies and on road cars to obtain maximum traction from the tires on the running surface. Suspension systems such as double wishbone, and trailing arm type are used on RIC model cars just as on full sized vehicles. absorb the energy stored in the spring upon compression. When adjusting suspension spring stiffness, then the damper



COIL SPRING **ADJUSTMENTS** Coil springs fitted to suspension units are there

to assist the suspension in following the surthat stores and dissipates shock energy to keep the car running steadily on the track. A too stiff spring results in an uncontrolled suspension that will cause the car to hop track. Springs should be adjusted according to the overall weight that compresses them. The coil springs included in the kits are designed standard performance. If the car is modified and trimmed for lighter weight, use a softer

soring. Springs should be stiffened using

spacers, after installing higher output motors. in order to compensate for the extra power. Using stiffer springs on rough terrain and softer springs on flat tracks is the normal rule. Car hops wildly and is not stall



Damper absorbs shock energy ADJUST DAMPER ACCORD.

ING TO SPRING STIFFNESS The dampers widely used in RIC cars are of the oil filled type. The higher the viscosity of the damper oil, the stiffer the damper, on the other hand, the lower the viscosity, the softer the damper. The Tarniya RIC spare parts, Damper Oil Set (50274), includes hard and soft type oil. The vellow is the soft and the red is the hard. Combining these two types of oil enable you to adjust your damper unit for various road conditions. When using hard springs use softer damper oil

MAKE SLIRE THAT ARM MOVEMENT IS SMOOTH Even though you have perfectly adjusted your

sion arm movement is going to spoil it all. Always maintain and make sure that the suspension arms move smoothly.

springs fitted and select springs that are slightly compressed with the weight of the car. Next. attach the oil dampers and press the car down and see if the car moves toward the at-rest position slowly. Bouncing back up is an indicaon the floor from a height of about 30cm and check to see that the car lands without bouncing or bottoming out, and that the springs aren't completely compressed. If this is attain-Do the final adjusting by actually running the car on the track to be used.

SUMMARY OF CAR CHARACTERISTICS Refore you become familiar with controlling

Corners" in "Building A High Performance Car'). Adjustment of toe-in and toe-out, tread teract closely. Test your car in various ways to find out the best setting for good control.

ENJOYMENT OF IMPROVING PERFORMANCE

As you attain proficiency in controlling cars you will be tempted to improve your car. This hapter will introduce handy ways of increasing performance. The most important matter you have to keep in mind when you modify it run faster. Still it cannot be an improvement turer with all factors considered such as speed, maneuverability and durability. So try to enhance the collective performance of your

LITH IZING AVAILABLE PARTS FOR IMPROVEMENT

ome car kits have optional tune up parts vailable on the market, such as more power. I motors, differentials and ball bearings. As in example, changing the 380 type motor for the more powerful 540 type will greatly increase the coeed of your model. Ball bearings are very effective in reducing the rotating friction of heels and axles, allowing more motor power to the driving wheels. On racing cars it is good ractice to replace the rubber like semioneumatic tires to sponge tires for better tracon. Different sponge tires are available for both the straight running ability and comerng simultaneously.

2. ADOPTING PARTS MADE You can also adapt repair and tune up parts

for other vehicles to your own vehicle. For example, the Tamiya Toyota TOM's Racing Master Mk.6 (58049) includes the 540 type motor, but ations at all. A speed controller without a diode in the circuit doesn't allow the use of the notor battery as a receiver battery also, thereby ightening overall weight. If you replace the peed controller to one with a diode, you can HANGING THE TIMES TO



Many sorts of parts are available on the market, other than radio controlled electric car parts. For instance, a type of push rod connecitems of other crafts besides model building and components of daily necessities can be

4 LIGHTENING WEIGHT Lightening the weight of a model car is another often done. Also, the windshield is made of thin

0.2mm transparent plastic plate, or only 1 battery unit supplies power to both the radio con-But radio controlled cars are subject to shocks

sturdily built 5 SLIPPI EMENTARY OF BATTERY POWER AND REMODELLING MOTOR

By increasing the number of batteries, improvement of performance can be achieved ture with thicker wire makes a motor rotate faster, but it will draw much more current. Also, filling up the gap between the armature and done by inserting 2 or 3 layers of cellophane Nevertheless, the motor is such a precision made item that these renovations may decrease performances or deteriorate the durabiliplaced under restriction; sometimes modifying







53001 Dynatech 018 mysy

S2037 H-Cap dam



QUICK DRIVE

RACING BUGGIES

MONSTER TRUCKS

QUICK DRIVE R/C SERIES With Tamiya's factory assembled, tested and

sion systems are damped with heavy duty coil springs for road hugging performance. Its sealed opar box, with precision differential almost ready-to-run Quick Drive radio controllkeeps out dust and debris, while the switch selected turbo option, allows high speed or ed models, all that is required to get you off and running is some simple assembly and battery mance. Tamiva offers high performance hop up installation. The Quick Drive RIC series allows you to get into the sport of radio control the easy space parts.



The Quick Drive series comes with a wheel and trigger, pistol grip type two channel transmitter that features proportional steering for absolute control. The electronic speed control uses proportional forward and reverse movement for utmost smoothness in operation. The transmitter is equipped with an indicator lamp that shows power availability.

DURABLE COMPONENTS

The Quick Drive chassis was designed for ruo-

ged use, and is made from light but sturdy engineering plastic. Both front and rear suspen-





Crystal identifications



POWER SOURCE

The Quick Drive series requires use of one (1) 006P size 9V battery for transmitter, and eight best performance, it is recommended to use intermix different types of batteries.

QUICK DRIVE SPARE PARTS OLECK DRIVE BOTH PARTS SET

Whether it's for repair or just enhancing looks a Quick Drive Body Parts Set is easily assembled and mounted on any Tamiya, bupgy type. Quick Drive chassis. All necessary parts, screws. and decals are included.



OD SLICKS F.A. R WWHEELS (43003) This is a slick tire & wheel set for the buggy type Quick Drive series. The fat slick tires provide positive grip when running on smooth sur-





OD PADDLE SPIKE TIRES FRONT WIWHEELS (43016) The QO bupgy paddle spike tire is designed to provide excellent wear and grip for, both on and off mad running. Front tire width is 28mm and diameter is 73mm





OD PADDLE SPIKE TIRE REAR WIWHEELS

road running. Rear tire width is 32mm and diameter is 73mm. Includes fashionable spoke



type wheels.

strength

QD GOLD MAG WHEEL SET F & R (43006) This set provides fashionable gold-color plated one-piece wheels for the front and rear ends of Quick Drive buggies. The wheels are injection molded in one-piece for lightweight and



OD MONSTER CV.A. SHOCK UNIT SET These are coil over oil filled shock absorbers for the Quick Drive monster trucks. Pistons and coil springs are especially chosen to take the extra abuse. One set contains parts for two



OD MONSTER GOLD WHEEL SET F & R This is a gold color plated wheel hub set for the QD monster truck series. Add a touch of class to your Monster Truck by using these eye catching wheels. Set includes one pair each for

OD MONSTER SPIKED TIRES 1 PAIR This is a semi-pneumatic, 114mm diameter spik-

ed tire set for Quick Drive monster trucks. The Set contains one pair of tires.

ADSPEC R/C

MEETING A NEW PARTNER FOR THE TRACK

Adspace "Advanced Specification" is a radio control unit designed especiality for 110 "125 scale RC models. Temiyals radio control modeling technology is fed had kin to this precision instrument for perfect control of your model. The Adspace RC unit is a partner you can rely on when you're out there on your own. Cell the ultross performance from your radio controlled models by use of this highly sochisticated RC system.

Surtery power level meter Seryo reverse switches Turnomitter Digital lap timer Steering trim



LAP TIMING AT YOUR FINGERTIPS

The system features a wheel and trioper type. pistol grip transmitter designed and sculptured through ergonomics to make all-day racing comfortable and effortless. The pistol grip is three-step adjustable for a firm orio when the competition heats up. The antenna is fully collapsible preventing accidental damage when not in use. A 1/100 second digital lap timer is neatly integrated in the steering wheel hub and the lap timer start/stop/reset buttons are ocated on the wheel edge for fingertin control letting you time yourself without any assistance. Other features include servo reversing switches, dual rate adjustment for precise steering, easily accessible frequency crystal, and battery power level meter

SAVE WEIGHT AND SPACE USING THE C.P.R. UNIT

Used in combination with the Adspec transmitfor is the compact CPR (Control Processing Receiver) unit P100F designed for 1/10 1/12 scale radio controlled models. The amplifier

C.P.R.UNIT P100F



boosted speed control is combined within the societier in this unit. The maximum curred aroper contains and 400 aroper immension, which is more than sufficient to accommodate the high power fechnigoid motions. Plus &V batteries are also compatible with the system. The speed control is linear reportions for forsess and and fixed for revense. Steering seen plugs Advanced specifications you can't allord to Advanced specifications you can't allord to see the second seed of the seen seen plugs.

issIt gets your empetition.	finger itching to trigger the
impetition.	
PR UNIT PIOUF SPE	programs
nge	Approx. 300m (surface operation)
wer supply	721 841
	50mA (with seno connected

handling capacity. 90A constant, 40DA momentary. Dimensions. 45 x 25mm Velepte. Approx. 65 x 35mm Velepte. Approx. 65 x 35mm Velepte. Approx. 65 x 35mm Velepte. 45mm Velepte. 45mm Constant Constant against ... One side 45 or greater including tres; Power supply. 43ft or 65% distance with received. Current connecuration ... 45mm Velepte. 45mm Velepte



TIPS FOR INSTALLING THE C.P.R. UNIT P:100F IN TAMIYA R/C MODELS

 This is a compact Control Processing Receiver (CPPR unit developed for 1/10 - 1/12 scale RIC models. The CPR Unit P-100F set contains, CPR unit, receiver switch, and separate steering servo.
 Installation for Tilemba RIC care is as follows.

HORNET

Out off speed control stay and antenna pipe mount as indicated and secure unit in place as shown using double sided tape.



BIGWIG Trim speed control servo stay parts A12 and

sub chassis as indicated and secure unit as shown using double sided tape. Route cables under the stay to avoid interference with center drive shaft.



PORSCHE 956, TOYOTA TOM'S 84C

Raise the mechanism deck 3mm placing spacers or washers between the six support stays, and secure unit in place as shown using double sided tape.



PORSCHE 959, TOYOTA CELICA Gr.B Apply a layer of 5mm foam board on

Apply a layer of 5mm foam board on receiver installation area on chassis, then install unit.



FOX Install unit in place of speed control servo in side mechanism box.



Secure in place as shown using double sided tape.



BOOMERANG, SUPER SABRE





LUNCH BOX MIDNIGHT PUMPKIN Secure unit in place as shown using double sided tape.



Secure unit in place as shown using double

sided tape.



BLACKFOOT MONSTER BEETI E Secure in place as shown using double sided



LOTUS HONDA 99T WILLIAMS FW-11B HONDA 21



MADCAP SAINT DRAGON Secure unit in place as shown using double sided tape.



GRASSHOPPER II Secure unit in place as shown using double sid-



Secure unit in place as shown using double sid



HANOUISH Secure unit in place as shown using double sid-



Secure unit in place as shown using double sid.



THUNDER SHOT, THUNDER DRAGON, FIRE DRAGON. TERRA SCORCHER

Secure unit in place as shown using double sid-



. The CPR Link RIDGE can be installed on all Tamiva RIC cars after the Lotus Honda 99T 58068 without modification. Earlier models

FI IMINATING RECEIVER BATTERIES

BEC TAMIVA BATTERY ELIMINATOR AND BEC

The battery eliminator equipped proportional unit referred to as BEC (Battery Eliminator Circuited was developed under cooperation with Tamiya and Japanese radio unit manufacturers in order to simplify the task of eliminating the receiver batteries. + Stop the car immediately when the battery

EQUIPPED PADIO LINIT

power drops off on cars utilizing the same power source for the receiver and motor to prevent the car from running out of controls.

REING LIGHTER MEANS GOING EASTER Usually your radio controlled car will need 4

LIM-3 dry batteries for the receiver. Eliminating the receiver hatteries means that the receiver ing battery. This not only makes your car direct power from the Ni-Cd battery provides quick response for the steering and speed controller. The receiver and servos operate on 6 volts. Therefore, when a 7.2V Tamiya Ni-Cd running battery is used for the receiver, the voltage needs to be dropped to 6 volts. The battery eliminator does just that, smoothing out the current providing a stable 6 volt current. The BEC system proportional unit is a radio unit that is equipped with the eliminator Normal radio units can be easily altered to eliminate receiver batteries by combining with Tamiya's battery eliminator.

THE EASY CHORE OF CONNECTING CONNEC-TORS TO FLIMINATE

Though not common, the modifications to eliminate receiverisery batteries were well known amongst experienced RC car enthusiasts by utilizing diode type eliminators. This modification carried some risks of wiring mishans which cometimes resulted in destroying the receiver unit. The REC system. proportional unit and Tamiya Battery Fliminator was developed to end the worries pin micro connector wired speed controller. the receiver batteries are easily eliminated without the bassle of any wiring chores what unneeded receiver battery connector and replace it with the Eliminator connector.



RECEIVER BATTERY ELIMINATING CONVERSIONS

. 6 different Tamiya battery eliminator units are

available for use with the 6 most wirtely us.

ed radio systems. Select one that matches

FOR YOUR TAMIYA BIC CARS

BFC

BEC

your radio system.

with BEC mark

aggie Bally

Porache 956

TOM'S 840





+2 Remove the kit supplied dode type receiver switch and

The Porsche 956 and Toyota TOM'S 84C are designed to ob-

Receiver battery (UM3 x 4) is necessary beside the

∢STANDARD RIC UNIT>

REC SYSTEM RADIO UNIT IN



BEC

POWER SOURCE

Tamiva Ni-Cd batteries utilize the tab-less system for obtaining the utmost current flow. resulting in swifter, more powerful acceleration and higher total performance. If the battery is handled correctly, it can be recharged more than 500 times. This makes it very economical. even though the initial purchasing price might seem high when compared to dry cell batteries As a nower source for BIC models Tambia nonvides Ni-Cd batteries ranging from the standard 6V1200m&h size to the high power 8.4V competition battery.

ing current -400nA . Standard charging time -14 - 16 hours -20°C to +60°C, On -30°C to +60°C • Or sions & weight - 50 x 54 x 37 mm, about 900 o 6V 4000mAh

ERY 72V-1200mAh

TEMPS NICE

charging current—120mA • Standard charging time—14 • 16

7.2VI200HAN RACING PACK

72V-1700mAh

TAMPA Ni-Ori 7.2V1700mAr

 Nominal capacity 5 hours — 1700mAh ● Nominal volta - 7.2V ● Final discharge voltage — 6.0V ● Standard charg — 724 ♣ Final discharge voltage — 6.07 ♣ Standard charging current — 360mA ♣ Standard charging time – 7 - 8 hour ♣ Semperature range — discharge: 20°C to +60°C, Charge 0°C to +45°C, Long presentation: 30°C to +35°C ♣ Dimen sions - 130 x 46 x 24 mm ◆ Weight - about 310g

TAMIYA Ni-Cd K CHARGERS



EXCLUSIVE QUICK CHARGERS FOR USE WITH TAMIYA NI-CD BATTERIES These are exclusive fully automatic chargers

designed for safety and reliance, for quick recharging of Tamiya Ni-Cd batteries. The chargers are powered from a cigarette lighter socket in a car which make them excellent for field use. The standard charging time is only fifteen minutes; short enough to recharge the battery during an interval of the races. When the charging is completed, the charger automatically switches off and the pilot lamp goes out. A different circuit is incorporated and whilst charging, the charger is constantly checking the state of the battery. Inadequate saturated battery cannot be damaged by con tinued charging. Also, the chargers are designed for safety against over-heating of both charger and battery. If any extraordinary heat off automatically. Safety is very important with

a quick charger, because it supplies a lot of current at a time. The size is about 11.1cm x 7cm x 5.5cm, weighing only 220 grams; very compact and easy to carry. The length of the input cord is 80cm and the outlet cord 35cm-long enough to use. The pilot lamp will light while charging and go out when the charging is complete as an extra safe quard. All in all the Tamiya quick charper features a safe and prudent design for

joyment of radio controlled cars.

84V-1200mAh **BOLD POW** s.ev *Prina discharge votage=-/2V *Standard charging time=-4-6 hours *Temperature rance=-Discharge: -20°C to +60°C Charge

65

* Bassivy to charge to charging—car cigarette lighter 1200mAh * Power source for charging—car cigarette lighter (12V negative earth) * Charging time—about 15 minutes * perature range for operation--0°C to 40°C • Charging about 220g * Length of input cord-800mm * Length of out

outer for change are considered with a Power source for changing—as regardles (phine 12V negative 4 nound) • Changing time—approx. 60 minutes • Temperature range for operation—9°C to 49°C • Changing capacity—100% • Resistance cord provided with overheating protection • Dimensions 111 × 10 × 55mm • -approx. 220g • Langth of input cord—1550r of output cord—350mm

HOW TO USE TAMIYA NI-Cd 8.4V-1200mAh GOLD POWER

THE GOLD POWER IS BEST SUITED TO 4WD CARS

4WD radio controlled cars are ideal for 8.4V

batteries since the enormous power is distributed through all 4 wheels enabling easier control of the car. Tamiya's Bigwig was designed to use the 8.4V battery, but if you are going to use it on our other 4WD cars, use the following parts to compensate for the extra power. Remember that more power means more wear and maintenance.

TECHNIQUED MOTOR FOR

In order to utilize the power of the 8.4V battery, a new motor was developed using the combined knowledge of the Mabuchi Electric Motor Company and Tamiya's radio control car experience. The RX-540VZ Techniquid motor was designed to get the utmost performance from the Gold Power battery, and provide the reliability desired by the serious enthusiast. Use a smaller pinion gear (13T - 15T) and always keep the motor maintained and tuned for the best performance at the track



O UP GRADE USING RALL

Plastic and metal bearings wear faster than ball bearings. Worn out bearings hinder gear electronics. Equip and upgrade the model using ball bearing set available separately.



OUSING BALL THRUST

Replace thrust washers and parts E11 with ball thrust bearings on the Hotshot, Supershot, Bigwig and Hotshot II. They reduce wear and transmit power efficiently.

THE 8.4V BATTERY

All the models have a 7.2V connector on the speed controller. Therefore an 8.4V Battery Adapter is required when using it.



HOTSHOT 8.4V BATTERY

This RAV Battery Holder can be used for the Hotshot, the Supershot and Hotshot II. The length is just right and screws easily into place.



Required parts	Ball bearings	Battery holder			
Thunder Shot Thunder Dragon Fire Dragon	RC Spare Parts 50073, 50041, 50064. Requires 24 ball bearings.	After position of battery holder (81)			
Terra Scorcher					
Hotshot II	RC Spare parts 50341	RC Spare parts 50296 8-FV Battery Holder			
	RC Spare Parts				

82--IL SXXIF H-CAP DAMPER SHOPE

OIL FILLED SHOCK LINITS

Both the CVA. (Constant Volume Adjustable) metal cylinder competition shock units contain a fixed volume of oil and use a compression relief oil seal. This provides the smoothest shock action while still giving optimum road hugging ability to the vehicle. Adjustments can be made at the coil springs, and pistons to compensate for differing track conditions. Oil viscosity can be altered by using the Tamiya

Silicone Damper Oil set, to obtain the best performance . Shock unit dimensions differ according to the vehicle. Refer to illustrations and notes.

1) SEEZ CVA MINI SHOOK UNIT SET

9 SINS CVA SHORT SHOOK UNIT SET (8) SERIS CVA SHORT SHOCK UNIT SET

5000 CVA LONG SHOOK UNIT SET

\$ 53036 H-CAP DAMPER MINE SLength can be changed using spaces

E SXXX H-CAP DAMPER MINI

(T) SXIST H-CAP DAMPER SHORT

HI-CAP DAMPER RACING

Set 50305-2: required for conversion to dual shocks at the If the series and mounts contained in hit when installing

© Set 50332 ① or 53036 ② required to convert to dual shock

For competition enthusiasts, Tamiya offers spring sets for Hi-Cap damper units. Each set contains 3 pair of springs with three different spring tensions, allowing damper set-ups for wide range of differing track conditions.



THUNDER SHOT

MENIGHT

COMPETITION MOTORS

For the serious racing enthulast, Tamiya. offers competition motors to get the utmost performance from your vehicle. These precision crafted motors are also designed to be easily serviced and tuned for obtaining the best results. at the track. Tune and adjust your vehicle to make use of the extra power, by hopping-it-up. with ball bearings, etc., and always replace any

worn parts immediately



Current drain at best efficiency 5000 DYNATECH OIR MOTOR





Timiya has available spare rotors and brushes. for their high performance competition motors. Even special wound rotors are available for those seeking maximum power. Disassemble clean and maintain your motor periodically, and change the rotor andior brushes to new ones I they are badly burned or worn.



ODUDODIONS CAUTIONS

HOP-UP OPTIONS For those seeking more performance at the track, Tamiva's Hop-Up Options provide the serious radio control competitor with race weight savings, and added durability. Enhance the overall performance and potential of your

Tarniva racer using these optional Hop-Up parts to meet your competition requirements.

TITANIIIM SCREW SET

In order to reduce overall weight of your racing machine. Tamiya offers titanium screws and aluminum nuts to replace kit supplied screws and nuts. Use these space-age components for a performance increase. -----

		=		-
				ь
		ᄫ		
		\equiv		
			=	
		-		
		_		
-			-	
		-		
			=	
-		-		
		-	=	
			00	
		-		
		- C		

UNIVERSAL SHAFTS

The universal shafts help transmit power more efficiently when compared with the convenis usually furnished stock on most RIC buooles.





Radio controlled cars have the potential to ex ceed speeds of more than 40km/h. The high power Ni-Cd batteries, precision radio units and high performance motors combined together make this performance possible, and none of these factors should be abused if your car is to perform up to its limits. Misuse of your equipment will result in damage to the car, as well as leading to unnecessary accidents. Always pay close attention in your handling of RIC models.

RUNNING THE CAR 1. FOLLOW CORRECT B/C **OPERATING**

Refore

SPEEDS

Follow the instructions outlined below when operating your RIC vehicle. They are important to prevent trouble and accidents.

Switch on transmitter → Switch on receiver → Connect running battery Disconnect running battery After running → Switch off receiver -- Switch off transmitter

2. NEVER DRIVE NEAR TRAFFIC OR CROWDS

You will be offending the traffic law if you run an RIC vehicle on the streets Some RIC models exceed speeds of more than 40km/h. Imagine a model colliding with a human at that speed. Serious injury is likely to occur.

3. RUNNING IN LOW SPEED FOR LONG PERIODS BURNS OUT RESISTOR «SPEED CONTROLLER AT LOW AND MIDDLE



pose and not for low and middle speed runn ing. Low and middle speeds are mainly used at tight comers as braking and for better ac

RIC model cars are designed for racing pur

celeration. The current flow from the Ni-Cd battery is bled off in the form of heat at the resistor when at the low and middle speeds. from the resistor or melting the resistor plate.

* Touching the resistor during running or after running the car can get you burnt + When the speed controller is in too speed the resistor is not impeding any current flow. therefore no heat build up occurs



4. NEVER DRIVE INDOORS AND IN CONFINED AREAS Running for long periods at the lower two speeds on the controller will cause the

resistors to overheat. Also the chance for collisions are much greater, so always drive your RIC vehicle in a wide area.

5. NEVER IMPOSE TOO MUCH OF A LOAD ON THE MOTOR

Getting the wheels stuck in a ditch, stopping the wheels from rotating on purpose, pulling or carrying heavy objects, unnecessary hill climbs, etc. will seriously damage or burn out the motor. Never impose too much of a load running battery power will drop off to a shorter running time with a slower top end speed which means you need to replace the motor . Motor may also burn out if adjustments at

gears and joints are improper.

6. YOU CAN'T CONTROL CAR WHEN BATTERY POWER DROPS OFF

A ratio controlled car will run out of control when either the noulever or transmitter hattery voltage drops off. The receiver does not have an indicate to indicate the remaining power, therefore earth attention is required. A car that is running unity the BEC system radio unit or the battery eliminator obtains receiver battery power from the running battery, iterefore stray power from the running battery, iterefore to slow down to prevent the car from running off uncontrollade.

ASSEMBLY AND WIRING

1. BAD SPEED CON-TROLLER ADJUSTMENT RESULTS IN RESISTOR HEAT BUILD UP

Make sure to check stop, low, middle and top speed positions of the speed controller with the radio unit. A speed controller arm that does not reach the top speed contact results in resistor heat build up.

2. TAKE MAXIMUM CARE IN WIRING, SECURING AND INSULATING CABLES

Make sure to properly insulate cables with heat shrink tubing supplied or virryl tapes (never use cellophane tape). An improperly insulated cable will result in a short circuit.

Marco

Stiff rotation of gears, shafts, joints and wheels results in motors burning out. After assembling gear box, check whether joint shafts rotate smoothly by rotating them us-

4. EXCESS VOLTAGE FLOW
DAMAGES MOTOR AND

SPEED CONTROLLER
Abide by using the prescribed and recommended voltage. Using excessive voltage Ni-Cd batteries damages or shortens the life of your motor, speed controller and other components.

REPLACE WORN SPEED CONTROLLER Speed controllers work under heavy current

Speed controllers work under heavy current flow, and worn contacts can be seen after many hours of running. Worn contacts add resistance. Check speed controllers periodically for wear, debris and dust on the contacts and replace the speed controller if

HOW TO TREAT YOUR NI-Cd BATTERIES

DISCONNECT BATTERY
 CONNECTOR AND
 REMOVE, WHEN NOT US-

ING THE CAR
Leaving your RC car with the battery connected when not in use, may cause the speed
controller to operate from other sources of
radio waves which could result in resistor heat
half un leaving on to diamage.

2. NEVER DISMANTLE OR SHORT CIRCUIT NI-Cd RATTERIES

Tamiya's high performance Ni-Cd batteries put out as much as 300 watts. Abuse, dismanting and tampering with cables may evoke overheating or meiting of the cables or battery case, and the battery itself is likely to be destroyed.

3. USE THE CORRECT CHARGER FOR CHARG-ING YOUR BATTERY

It is important to have the correct charger to enable you to obtain the very best performance possible from your battery. Over charging the battery not only damages the battery but may result in excess heat build up and the When either the battery or the charger boomes overheaded during charging, stop the procedure and take it to the shop of purchase for inspection.

ABIDE BY THE CHARG-ING INSTRUCTION OF YOUR CHARGER A specific length of cord involuced with a

designated resistance value) is used on the input side of the quick chapper for the Ni-Cd battery. This cable should not be cut, otherwise the resistance value will vary and the cable will heat up and melt. Also, do not attach any connector clip anywhere on the cable.

REVERSE CONNECTION DESTROYS CHARGER

Most damage done to a charger can be aitributed to revene polarity connections. Enomous current flows through the circuit berween the charger and the battery at the moment of the connected in reverse Arc overhigh trickle current file of the connected to the the moment a heavy current is fed into the circuit from a wrong connection, it will burn out the circuit. The Tally applied uses an exclusive connected the connected to the contraction of the connected to the connected to the contraction of the connected to the connected to the contraction of the connected to the connected to the contraction of the connected to the connected to the connected to the contraction of the connected to t clusive plug so that only the correct charger may be used on that battery. When the quick charger is used for the Tamiya, When the quick charger is used for the Tamiya, Ni-Gb battery, you are required to watch not only the direction of the connectors, but also potarity of the 12 volts power source inequal potarity of the 12 volts power source inequal earth, Mistakes will cause the battery to burn out and become useless.

An overnight type charger shows a difference in voltage from 35 to 45 votts when measured between the terminals without a battery corrected. This indicates the charger works correctly. In the case of quick charger, it does not read any voltage; this is a normal condition, if the pilot lamp is on.

it does not read any voltage; this is a no mail condition, if the pilot lamp is on.

6. NEVER RECHARGE BAT-TERY WHEN THE BAT-

TERY IS WARM
In most cases the Ni-Cd battery will become heated during use. Cool off the battery before commencing recharging to avoid damage.

7. WHEN USING QUICK CHARGER FROM THE CIGARETTE LIGHTER IN YOUR CAR, PLACE BOTH THE BATTERY AND THE CHARGER ON THE FLOOR

Not on dashboards or seats where they are unstable.

8. DISCONNECT BATTERY CONNECTOR WHEN

YOU'RE NOT USING THE CAR AND SWITCH OFF RECEIVERTRANSMITTER After finishing running your RC car, make sum of the control of th

or overheated resistors and burning cables.

9. WATER IN THE BATTERY
Water which penetrates into a battery may
cause a short circuit or commode the internal
wiring when the electricity flows through the
wet wiring. Therefore, if the battery becomes
wet, stop running the car and dry the battery
completely.

10. PULL OUT CHARGER PLUG AFTER USE

 NEVER INCINERATE US-ED BATTERIES

Lack of attention to your RC equipment may lead to unnecessary trouble. Take the utmost cautions in handling your RIC cars for long lasting enjowment.

MAINTENANCE MATERIALS

TAMIYA SPRAY OIL



Tempa Spery Oil is an Oil which utilizes a the USA, which has present effective as a long liasting lubricant. As It has strong being being being the service, within paths, providing a smoother and less flow paths and the path of the paths of the operation than normal penetrating buffcars. If the paths of the paths of the penetration of the paths of the paths of the paths of the Spray Oil onto the chassis or other metal saver and the metal surface to form a layer which helps to dry up the surface and also protects the metal from rusting and so protects and so protects and also protects and and so protects

LIQUID THREAD LOCK

EXECUTION DIRECTOR OX

It is essential that this liquid thread lock be applied to all nuts and screws when the model is assembled. This liquid is not all glue, but a securing agent, it will prevent screws from working loose, which will happen if it is not used. It is every effective and easy to use. At any time, screws can be loosened or removed for maintenance or repairs by using about twice the force recuired when they were originally tiplithered.

BALLDIFFGREASE



RIC enthusiasts for their ball type differential gear units. It is specially formulated to prolong component life while maintaining the proper transmission torque. The long nozzle on the tube allows easy application. NOTE: Use only on ball type differential gear units.

DOHO OTRATE



Vour speed controller, in order for it to do the copy of the controller, in order for it to do the copy of the controller or the controller or the control. This switch lubricant of the tenumitter control. This switch lubricant will provide you win a speed controller that responds correctly each and every time. The lubricant also helps to suppress the ancing that is always present, in any high current flowing switch, and will prolong its life fair longer than expected ong its life fair longer than expected switch lubcicant is also sale with plastics and market lubcicant is also sale with plastics and present controller is sent in more controller.

steering, so use the lubricant periodically to ensure proper performance of your RIC car and to prolong its life.

HERMINIA CHEMST

This grease is formulated using Boron Nitrola practices, and is ideal for use on electric powered RC vehicles. It should be applied to all bearings, white and pears where about plastic comosion is done away with throrise about plastic processes will substantially protong the file of your Processes will substantially protong the file of your RC vehicle and less pit performing at its best. Each tube contains 'RQ of lubricant, and the amount in those hard-loreach amass.



PAINTING OF R/C CAR BODIES

A large part of the enjoyment of RC cast is in the construction and unning of the well-cite; however, the final finishing and painting cars also provide great deleases. He clear for the clear final finishing and painting to make the clear figuratest challenge in painting to most modelen because they are not familiar self-incodes because they are not familiar self-incodes and the control of the clear finishing to the clear finishing to the clear finishing and card card on the demanged during hard accidents on the track. Polycam finishing and card card to the demanged during hard accidents on the track. Polycam finishing the clear finishing and card card to the demanged during hard accidents on the track. Polycam for the clear finishing and the finishing and t

SOME HINTS ON PAINTING

vacuum formed.

If you have a choice, paint on a clear day with little humidity. Painting on a damp day will leave the finish cloudy or milky due to "Blushing"

* Ventilate the painting area by opening a

 Ventilate the painting area by opening a window.
 Never paint near an open flame.
 Spray paint outdoors in a windless area.



AINTING OF INJECTER

MOLDED BOOIES
These bodies are made from shock resistant styrol and are from the same basic material as plastic models. Suitable paints are the Tamiya Acrylics, Paint Markers or other paints for plastics.

9 Preparation

You must remove all dust and oil from the surface of the plastic by washing it well with a kitchen detergent, then rinsing it off with clear water and drying thoroughly. All of the parts that are to be painted in the same color are gathered together in one place. Joint and seam lines are cleaned up with a modeling Clean up joint and seams with.



knife and sanded down with very fine finishing paper. Hold the small parts for painting with a spring clip. If spray painting, set the parts on a box or stand to make it easy. ② When painting many colors

(2) When painting many colors When you are adding stripes or doing different contrasting colors, masking of the areas is vital. Use only a high grade of paper masking tape, not the masking tape used for full sized vehicle painting. Frisket paper and paper tape is available from good hobby shops and art stores. Remember the colden rule of painting outside surfaces: Always paint the light colors first, then go on to the darker colors. Mask small areas at a time. When doing a large area, cover it with newspaper, masking the edges of the paper with tape. When doing curves, place the tape into position, then draw in the curve with pencil, cut and remove the unwanted areas of tape with a modeling knife. Press the edges of the masking tape down firmly with your finger or toothpick.



For finishing large areas, spraying is easier and the results are better. Remember to use the light colors first, then on to the darker shades. Remove any masking just prior to the paint becoming completely dry. Add any detail painting and the driver figure. Polishing with a compound will add a high closs finish.



OSpray pa

Spray paint about 30cm from the model.
 Spray a light coat for good paint adhesion.
It will dry faster and you can add another coat in a few minutes.

 When the distance between can and model is too close, or you try to do a thick coat to finish quickly, you will get runs, and the paint will not adhere to the plastic properly.

Brush painting hints

 ★ Select the brush according to the job. Use a wide flat brush for large areas, and a fine, pointed brush for detail work.
 ★ Paint only in one direction. Never back and forth like a house painter.
 ➤ Don'the concerned about biotiches or mans.

at this time. Leave them and overpaint the area after it is completely dry.

Some practical advice Bright colors, such as red, yellow and white, do not look good if painted over a dark color

such as blue or black. Paint the surface first in flat white, then the finished red, yellow etc. will be bright.



bodies (LEXAN)

Lightness and toughness are features of polycarbonate bodies. Special paints are required for finishing these bodies. Normal plastic paints and lacquers will peel or high off even with the slightest shock to the body so if it is necessary to utilize polycarbonate paints especially formulated for this purpose.

Out of the extra portions of the body using a sharp kine, by sortiling in one stroke, on the parting line. Bend the extra wavy from the parting line. Bend the extra wavy from the controlled line and it will snap or tea ord perfectly. Use only a very sharp kine for scribing, the sharp kine for scribing and sharp wave the sharp vocan imagine. After trimming the body to the and all of the initials our large sincept the window areas) with 400 grif finishing paper. This will provide a pool base for the paint. When sanded, wash the entire body with detergent, rinne and let dry.



(2) Masking.
As in painting styrol bodies, masking is necessary when using more than one color.
As painting will be done on the inside sur-

faces, it is done in reverse. Paint all the details Paint the darker colors first, followed by the lighter ones. If spray painting also, you must mask off the entire outside surface of the . Paint small details first, (Window, panel lines, etc.)





As paint is applied from the inside, but viewed from the outside, the first coat (details)

must appear as the outer most color when sider the order of your painting to achieve this effect, and as it is applied just the opposite from painting styrol bodies, you have to be thinking about it all the time. · Mask all windows and the outside







Hold the spray can about 30cm away from the body and spray the same as when doing styrol bodies. Check from the outside to make sure that you have covered all areas required If the painted surface is uneven, let it dry and correct it later with an additional coat. When several coats are to be applied, let each dry thoroughly before applying another coat.

When the polycarbonate paint has dried it has a very strong film surface and the masking tape will tend to pull away the painted parts on the model. The masking tape should ly. If the paint starts to peel away from the body while removing the masking tape, take a sharp knife and run the tip along the tape edge to free it from the painted surface, and ing the paint from the surface.

Hints for finishing

Until the latter half of the 1960s, the racino cars at the International Races were painted in National Racing Colors which were desigof sponsoring companies or the design of the merchandise package. Among the well known blue: a design from a cigarette pack in the black and vellow of the JPS Lotus: red and white of the Mariboro McLaren. Think out your own design, assuming you were a sponsor-

The following is a list of some National 2 tones Red and White

USA 2 tones Blue and White Italy Blue Germany

Japan

Belgium

Stripes of Blue and Silver

R/C BODY MAKE UP FOR PREPARATION PRIOR TO PAINTING The decoration and finishing of RIC car bodies is not only self satisfying, but an essential

part of the construction of radio control models. A heautifully finished car seems to run faster than the others and if it is an original or remodeled vehicle it will stand out conspicuously. Tamiya has made available almost all of the finishing material needed to produce a highly realistic model. They are of the highest quality, easy to use, and available from your local hobby supply house. Modeling brushes for painting; putties for repair; epox ies for remodeling; compounds for preparation These, and other Tamiya materials will assist you in producing a lifelike masterpiece for your enjoyment.

For brush painting TAMIYA MODELING BRUSHES Tamiya produces 7 quality modeling paint

brushes. They fit the hand easily and are easy to control when painting. 3 flat brushes for large painting areas. Number 5 has a width of 15mm. Number 3 a width of 8mm and Number 0 a width of 4mm. Four pointed detail brushes are available. Two from high grade from high grade weasel hair. These brushes will satisfy the most discriminating modelers. Printed Brush High

For preparation prior

TAMIYA FINISHING ABRASIVES This is a new clog resistant, wet or dry finishing paper These types of abrasive papers are necessary for preparation of polycarbonate bodies prior to painting and also for sanding down to final shape any the speed controller clean and polished, for better control. A medium grade set is available for wood finishing, and a fine grade and a ultra fine grade sets for plastic and metal



one sheet of #600 ● Litra Fine Set #2000, #1500 two sheets each and one sheet of #1200 Making small parts

TAMIYA EPOXY PUTTY This is a two part putty that can be formed just like clay. Knead the two equal length outty parts together with your fingers. It will begin to harden in about an hour and will be completely cured in 12 hours. It can be carved with a modelling knife and sanded to final shape with finishing abrasives. It is useful for remodeling and repairs of plastic models. TANKA PENGETON

STOMBYA COLO GROSSY RESULVI

For filling holes and This is a soft, paste type of putty useful for filling holes and seam lines. It has low shrinkage and excellent adhesion on styrol type plastics. Quick drying!

For original body

PLAPLATE (WHITE AND TRANSPARENT) These are sheets of styrol resin in the 84 size. can be used. This plastic sheeting is excellent for modifications, repairs and original body

construction. Available size are: Pla.Plate (White): 12mm 05mm 03mm Pla-Plate (Transparent). 1.7mm, 0.5mm, 0.2mm

Modifications and repairs in

PLA-PAPER 0.14mm & 0.27mm This is a chemically coated plastic paper that has the strength of polystyrene plastic and the flexibility of paper. It can be cut easily with scissors into any desired shape and bonds well with plastic cements. It is easy to write upon decorate with pencils, pens or paints, and has many varied uses to suit your modeling pleasure. PLASTIC REAMS ROUND AND SOLIARE

round cross section. Compatible with the Plaplate plastic sheets, these beams are easy. to work and use in conjunction with repairs and modifications of bodies and framework. The material is easy to form, cut and bend for complex curves and will retain its shape. after forming. Plastic Beam Square

2mm, 3mm, 5mm (Length: 40cm) Plastic Ream Bound 2mm, 3mm, 5mm (Lenoth: 40cm) CLEAR PLASTIC PIPE 3mm, 5mm & 8mm

These are crystal clear polystyrene plastic pipe that can be reformed, stretched, bent or shaped with light heating, providing tremendous versatility in your modeling and hand crafting endeavors. It can be bonded with plastic cements, painted with any of the plastic Each pipe is 40cm in length.

For a hand rubbed finish! TAMIYA BURRINGIPOLISHING COMPOLIND


Nothing looks guite as good as a hand rubbed painted finish, so Tamiya has added a rubbing and polishing compound to the growing line of finishing products. Painting over a rough surface will leave the finish rough, so preparation prior to painting is very important. With this rubbing compound you can prepare the surpound contains minute particles of abrasives. suspended in a cream. It is good for removing parting lines on the plastic, finishing up puttied areas or correcting and eliminating glue joints. Fine scratches and blemishes on clear plastic parts, such as windshields and aircraft canopies, can be completely removed. Use it

for polishing out the cloudy surfaces of lac-

quer paints and for adding a deep gloss to

acrylics. +NOTF: Not recommended for use

on Tamiya Paint Marker finishes.



Per Ind in pice

forcement. After finishing construction from figures 1 through 3, mount the body on the chassis and choick for any interference with the mechanics and wheel components. Also at this time, sorbs the body mount position and drill firm holes. When body assembly is done, said off and amount out degles, Apply putty to reproduce the curves and to cover up unwanted neam lines.

3. PREPARING FOR

CONSTRUCTING SP

Areas that have been putted or sanded hasely was a second or sanded hasely of friething absolves to totally eliminate the outputses, to a smooth finish, had smooth finish prior to painting will enhance the overall finish when paint is applied. Use two panels for the rear spolier parts and cement them together to make the spolier. Softich lightly, heat, and bend edge of spolier, and finish off for painting by smoothing out design.



4. PAINTING AND ATTACH-

Spray painting is recommended for overall painting of the body, Remove all dust and oil painting of the body, Remove all dust and oil from the surface poir to painting ingerts to PRIN-Till Fig. 1997. The painting is sufficient to PRIN-Till Fig. 1997. The painting is sufficient to PRIN-Till Fig. 1997. The painting is sufficient to the painting is painting to the painting is sufficient to the painting is to the painting is sufficient to the painting is painting to the painting to painting to the painting to painting to

beams.







E STATIONAL

After finishing with the painting, apply the finishing touch by attaching may spoiler and headlights. Use plastic material and clear The example shows clear plastic pipe used on sociler mounting and for exhausts, 2mm square beams are used to reproduce the engine grille located at the rear of the driver's compartment (figure 3). Even your own imaginative dream car can look just as real by adding details referring to photographs of fullsized evotic cars. Window frames and panel The Twota TOM'S chassis does not have a proutilizes a practice bumper used on the 1/12 scale R/C Porsche 959. Scratch built bodies are vulnerable to collision, and therefore it is essential to use bumpers for protection of your orininal body Using scrap parts and decals from the same sized scale models will add that



final touch toward realism.




















TAMIYA COLOR

BECAUSE THEY ARE WATER-SOLUBLE BUT PERMANENT WHEN DRY CLEAN

UP IS BOTH QUICK AND EASY WITH PLAIN WATER permanent and water will have no effect on

THINNER IS USEFUL FOR SPRAY PAINT ING AND THE FLAT BASE WILL TONE

EXCELLENT WHEN TWO OR MORE COLORS ARE REQUIRED FOR SPECIAL

camouflage, is quite easy as the pre-Acrylics can be painted over any other type

. Mix paint by gently stirring. Shaking bot tle will cause bubbles.

CLEAR COLORS PROVIDE NEW YERSA

Tamivals Acrylic color line contains six lights, and you can use the smoke shade

TO PROVIDE A REALISTIC METALLIC

When applying clear smoke color to the pearance of being used. If a small amount of flat base is added, this technique is very ing the clear orange and blue to the exthe real machines. Painting yellow or them into gold or copper plated fittings.

CLEAR COLORS WILL NOT HIDE THE

DURABLE FINISH

. Clear colors can be mixed with other clear colors for different shades and can



ers, it is indispensable for detail painting glass as well as on all plastics. Contents

EXCITING NEW RELEASE FOR FINISH ING MODELS OF PLASTIC AND OTHER against a firm surface to break seal and sures you of safe, easy painting without

PAINTING OF ROTH NARROW AND WIDE Model painting and detailing with a brush to detail your subject like never before. The the narrow edge to paint small areas. paint projecting parts with no overflow. cessories on military models, lights and

tip can be out to a desired thickness by		
TAMES	A PAINT MARK	ER 12 COLORS
XI	Riack	Gloss finish
X2	White	Gloss finish
X	Royal Blue	Gloss finish
X5	Green	Gloss finish
XS	Orange	Gloss finish
X2	Red	Gloss finish
X8		Gloss finish
XII		
X12		
XF1	Flat Black	Matt finish
XF15	Flat Flesh	Matt finish

USE IN COMBINATION WITH TAMPIA ACRYLIC PAINTS.

NUMBER AS TAMIYA ACRYLIC PAINTS.

TAMIYA COLOR

to beautify your clear car bodies.



EASY TO USE, SAFE AND WATER RESISTANT, PERMANENT AND

1/10 SCALE RADIO CONTROL CAR

Monster Beetle

Saint Dragon Ferrari F185 Late Version

Mercedes Benz CH

98096 Toyota Celica CT-Four Raily

1/12 SCALE RADIO CONTROL CAR

1/14 SCALE QUICK DRIVE R/C SERIES

58059 Porsche 959

Tamiva polycarbonate paints are water removed from brushes and other im-

EXCELLENT COVERAGE MAKES FOR

It is important when painting polycar

MIXING OF COLORS AND OVERPAINT ING IS FASY

sharker. When using masking tape, remove

useful for removing cured paint from .The painted surface will remain

TAMINA COLOR BOTTLE PAINTS



Si-Cd Battery Suick Charger SV-4000mAth

2V-275mAh Tampack Baltery 2V-275mAh Tampok Guick Charge

Persone MC 48002 Lancia LCZ 48000 BMW CTP 48004 Fred Mustane Probe CIP 47005 48005 Ferrari Testanossa 47006 48006 Porsche 961 OLUCK DODGE SPARE PARTS

Maria Ray Of

1/16 SCALE R/C TANK SERIES West German Leopard A4 Tank West German Flakpanzer Gepart

1/24 SCALE TAMTECH R/C RACING CARS

43000 GD Monster Gold Wheel Set (F & R) 43000 GD Monster Spiked Tires (7 par) QD Monoter Spiked Tires (1 pair) Dash-1 Emperor QD Body Parts Set Dash-3 Shooting Star QD Body Parts Set GD Black Motor Sush-G Wonzon GD Body Parts Set

Manta Ray QD Body Parts Set Q) Public Spike Tires Front (with Arm Spoke Wheels)



TAMIYA RADIO CONTROL GUIDE BOOK





